



Texas Education Data Standards (TEDS)

Section 9 v3 TSDS Unique ID Specifications

These specifications are valid *beginning* April 2, 2018

March 1, 2018

Prepared by: Information Technology Services Business Management Division

Table of Contents

Rollout Plan.....	1
TSDS Unique ID Batch File Format.....	2
Filename	5
Header Record Layout.....	6
Detail Record Layout	7
Trailer Record Layout	8
TSDS Unique ID Web Services Technical Guide.....	12
About This Technical Guide.....	13
About Web Services	13
IDAssignmentV2- Assigning/Retrieving an Identifier	14
Process Flow Example†	14
Operations.....	14
assignId.....	15
Reference WSDL	32
IDAssignmentV2 Transaction Status Table.....	33
NearMatchListV2 - Retrieving Near Match Lists.....	35
Process Flow Example†	35
Operations.....	35
getNearMatches.....	35
Reference WSDL	39
NearMatchListV2 Status Table	40
NearMatchResolutionsV2 – Near Match Decisions	40
Process Flow Example†	40
Operations.....	40
cancel.....	40
assignId.....	40
createNewID	41
Reference WSDL	42
NearMatchResolutionV2 Object Status Table	42
StudentSearch – Searching for a Student / Staff.....	43
Operations.....	43
searchStudent	43
Reference WSDL	54
Search Status Table	54
BatchInfoSearch – Searching for a Student / Staff.....	55
Operations.....	55
getBatchInformation	55
Batch Statuses.....	55
BatchInfo Search Status Table	57
Appendix A – Soap Message Examples.....	58
IDAssignmentV2 Request – New ID Example.....	58

IDAssignmentV3 Request – New ID Example.....	59
IDAssignmentV2 Response – New ID Example.....	59
IDAssignmentV3 Response – New ID Example.....	60
IDAssignmentV2 Request – Match List Found Example.....	61
IDAssignmentV3 Request – Match List Found Example.....	62
IDAssignmentV2 Response – Match List Found Example.....	62
IDAssignmentV3 Response – Match List Found Example.....	63
NearMatchListV2 Request - Existing Near Match List.....	63
NearMatchListV3 Request - Existing Near Match List.....	64
NearMatchListV2 Response – Existing Near Match List.....	64
NearMatchListV3 Response – Existing Near Match List.....	66
NearMatchResolutionV2 Request – Create a New ID.....	67
NearMatchResolutionV3 Request – Create a New ID.....	68
NearMatchResolutionV2 Response – Create a New ID.....	69
NearMatchResolutionV3 Response – Create a New ID.....	69
NearMatchResolutionV2 Request – Assign ID with error.....	70
NearMatchResolutionV3 Request – Assign ID with Error.....	70
NearMatchResolutionV2 Response – Assign ID with error.....	70
NearMatchResolutionV3 Response – Assign ID with Error.....	71
NearMatchResolutionV2 Request – Cancel.....	72
NearMatchResolutionV3 Request – Cancel.....	72
NearMatchResolutionV2 Response – Cancel.....	72
NearMatchResolutionV3 Response – Cancel.....	73
Error Response Samples – Invalid Username/Password.....	74
Appendix B – WSDL for Web Services.....	75
BatchInfo WSDL.....	75
IDAssignmentV2 WSDL, operation assigned.....	77
NearMatchListV2 WSDL, operation getNearMatches.....	81
NearMatchResolutionV2 WSDL, operations: cancel, assignId, createNewId.....	84
StudentSearch WSDL, operation search.....	87
Appendix C – WADL For Restful Web Services.....	91
Appendix D – IDAssignmentV2 Code Basic Example (VB).....	98

ROLLOUT PLAN

Task	Date
Unique ID v10.3.0 Released with Enrollment Functionality Enabled	April 2, 2018

TSDS UNIQUE ID BATCH FILE FORMAT

Detailed below are the specifications of the TSDS Unique ID Batch File Format. This file format must be followed when submitting students/staff for id assignment or enrollment event data (input file). The Batch File should contain three different categories of information and conform to the file naming conventions. The three categories of records are:

- Header Record
- Detail Record
- Trailer Record

The Header and Trailer record should be delimited by a single tab or space character. The Trailer shall have no empty spaces or data after the last Trailer column.

The same file format will be followed when the TSDS Unique ID system generates a file with the TSDS Unique Id number assignment (output file).

Filename

For each Batch file submitted, the system must identify the correct organization and data collection to process the file correctly:

Student:

Position	1-6	7	8-10	11	12-18	19	20-31
Description	District Code	_	Campus ID	_	Collection Code	_	Timestamp

Staff:

Position	1-6	7	8-10	11	12-16	17	18-29
Description	District Code	_	Campus ID	_	Collection Code	_	Timestamp

Enrollment Event:

Position	1-6	7	8-10	11	12-18	19	20-31
Description	District Code	_	Campus ID	_	Collection Code	_	Timestamp

District Code: The LEA code for which the data is being uploaded. (6 digits in length)

Campus ID: The campus ID for which the data is being loaded. If loading data for the LEA, use "000" for campus ID. (3 digits in length).

Collection Code: The collection code is a character string that uniquely identifies the data collection. (5-8 characters in length).

- The Collection Code shall indicate the type of data being submitted. The values are:

“STUDENT” which represents the Student data.

“STAFF” which represents the Staff data.

“ETEVENT” which represents the Enrollment / Withdrawal Event data

Timestamp: The timestamp is a date in YYYYMMDDHHMM format (e.g. 201406021015). The Timestamp shall be a system generated value at the time the data is extracted. (12 digits in length)

There **must** be an underscore (_) between each element in the file name.

Examples:

227901_002_STUDENT_201201241015 = Student Data for Austin High School in Austin ISD.

227901_000_STAFF_201201241159 = Staff Data for Austin ISD.

227901_000_ETEVENT_201803051225 = ET Event Data for Austin ISD

Submitting ETEVENT Records

2017-2018 Enrollment Event Submission Timelines (April 02 – July 31, 2018)

The first enrollment event file submitted through the Unique ID system should contain all enrollment and withdrawal events occurring after the last PET file was uploaded in March. All subsequent files should only include new or updated enrollment and withdrawal events from week to week.

Enrollment event files should be submitted each week an LEA is in session based on the local instructional calendar when there is any enrollment or withdrawal activity. Timely and accurate enrollment data aids all LEAs in locating students for data reporting and student record requests. Enrollment event files are not required in weeks that an LEA is not in session for at least one day or during the weeks that PEIMS submissions are due to TEA.

At the beginning of each school year, a cumulative enrollment event file will be loaded. This file will contain all students enrolled at the beginning of the school year. After the initial cumulative file is loaded, TEA strongly discourages the submission of cumulative enrollment event files. Only those enrollment and withdrawal events with event dates since the last enrollment event file was successfully loaded and processed into the Unique ID system should be included.

A valid Unique ID is required on each enrollment event record as this is the only matching criteria used.

Header Record Layout

The header record should always be the first record. Each of the fields should be delimited in the header by the field name reference below. The header record contains the following fields:

Field Name	Delimiter	Required	Data Type	Format Details
Record Type		Yes	VarChar (2)	The Record Type Value must equal "TH".
Extract Date		Yes	VarChar (10)	The Extract Date must be in one of the following formats: <ul style="list-style-type: none"> • mm/dd/yyyy • m/d/yyyy • mm/d/yyyy • m/dd/yyyy • yyyy-mm-dd
Extract Time		Yes	VarChar (8)	The Extract Time must be in the following format: <ul style="list-style-type: none"> • hh:mm:ss
Transmission ID		Yes	VarChar (10)	The Transmission ID is a number utilized by the submitter for auditing as an identifier for the submitter.
Version		Yes	VarChar (10)	The Version Value must equal "3.0".
Delimiter	delimiter=0X2C	Yes	VarChar (4)	The Delimiter must be a comma delimiter, the character literal would be "delimiter=," and the hex representation would be "delimiter=0X2C".
Source Name	source=	Yes		The Source Name value must equal "SIS" or "HR". If a source is not provided in the header, the file will be rejected.
Text Qualifier	qualifier=0X22	Yes		The Text Qualifier must be the text or the hex representation of the text qualifier that is used in the detail records (double quote only qualifier=0X22)

Detail Record Layout

The detail records appear between the header and trailer records. Each of the fields should be delimited even if data is not available for certain fields. These records should represent the individual student/staff/enrollment event data and should contain the following fields:

Field Name	Required	System - Data type	Used for Matching	Notes/Format Details
Record Type	Yes	VarChar(2)	n/a	The Record Type Value must equal 'ID'.
Current School Code	Yes	VarChar(9)	No	School Code where the student is currently enrolled or where the staff is currently employed. Indicates the unique campus number registered with the Texas Education Directory (askTED). Note: For non-campus staff, submit 000 as the last three digits of the Current School Code (for example, 227901000).
Reserved Field	No	VarChar(20)	No	Not used by TEA. Leave this field blank
Last Name	Yes	VarChar(25)	Yes	Legal last name of the student or staff.
First Name	Yes	VarChar(17)	Yes	Legal first name of the student or staff.
Middle Name	No	VarChar(14)	Yes	Legal middle name of the student or staff.
Name Suffix	No	VarChar(1)	No	Valid Values: 1 (Jr), 2 (Sr), 3 (II), 4 (III), 5 (IV), 6 (V), 7 (VI), 8 (VII), 9 (VIII), A (I), B (IX), C (X).
Gender	Yes	VarChar(1)	Yes	Valid Values: F (Female) or M (Male).
Date of Birth	Yes	VarChar(10)	Yes	Valid Formats: <ul style="list-style-type: none"> • mm/dd/yyyy • m/d/yyyy • mm/d/yyyy • m/dd/yyyy • yyyy-mm-dd
Current Grade Level Code	Yes	VarChar(2)	No	Valid Values: EE (Early Education), PK (Pre-Kindergarten), KG (Kindergarten), 01 (Grade 1), 02 (Grade 2), 03 (Grade 3), 04 (Grade 4), 05 (Grade 5), 06 (Grade 6), 07 (Grade 7), 08 (Grade 8), 09 (Grade 9), 10 (Grade 10), 11 (Grade 11), 12 (Grade 12), and 00 (only valid for Staff).
Local Student ID	Yes	VarChar(9)	No	ID used in the local Student Information System to uniquely identify the student in the submitting system. The primary purpose of this field is to provide a mechanism to import student data from the TSDS Unique ID system back into the local source systems. For staff, ID used in the local Human Resource System.
Social Security Number or S-#	Yes	VarChar(9)	Yes	Student or Staff Social Security Number. Or, state-approved alternate identification for student
Race	Yes	VarChar(1)	No	Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White).
TSDS Uniq-ID	No	VarChar(10)	No	This field is the assigned unique id and is provided in the output file produced by the ID assignment file process, therefore it should not be provided in the ID assignment file input. The TSDS Uniq-ID field is required in the ETEvent records. This value will be ten significant digits and will not begin with 0.

Field Name	Required	System - Data type	Used for Matching	Notes/Format Details
Current District Code	Yes	VarChar(6)	No	District code where the student is currently enrolled or where staff is currently employed. Indicates the district identification number registered with the Texas Education Agency.
Current School Year	Yes	VarChar(4)	No	Valid Format: YYYY. Represents the latest year in the school year range. ("2013" for the 2012-2013 school year).
Alternate Last Name	No	VarChar(25)	No	Maiden Name of Student or Staff.
Reserved Field	No	VarChar(50)	No	Not used by TEA. Leave this field blank.
Reserved Field	No	VarChar(60)	No	Not used by TEA. Leave this field blank.
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Ethnicity Indicator	Yes	VarChar(1)	No	Valid Values: 1 or 0, 1 indicates a person of Cuban, Mexican, Puerto Rican, South or Central American, or other Spanish culture or origin, regardless of race. 0 indicates a person not Hispanic/Latino.
Race 2 Code	No	VarChar(1)	No	Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White). See Example.
Race 3 Code	No	VarChar(1)	No	Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White). See Example.
Race 4 Code	No	VarChar(1)	No	Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White). See Example.
Race 5 Code	No	VarChar(1)	No	Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White). See Example.
Reserved Field	No	VarChar(10)	No	Not used by TEA. Leave this field blank
Reserved Field	No	Varchar(60)	No	Not used by TEA. Leave this field blank
Reserved Field	No	Varchar(100)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(60)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(50)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(50)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(30)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(30)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(2)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(17)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(22)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(20)	No	Not used by TEA. Leave this field blank
Reserved Field	No	datetime	No	Not used by TEA. Leave this field blank

Field Name	Required	System - Data type	Used for Matching	Notes/Format Details
Reserved Field	No	VarChar(20)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(20)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(125)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(20)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(2)	No	Not used by TEA. Leave this field blank
Submission Purpose	Yes	VarChar(3)	No	Indicates the type of data in the input file. Use Assignment if assigning Unique IDs; Use Enrollment Events if submitting enrollment or withdrawal data: 001 – Assignment 002 – Enrollment Events This field is mandatory for every Enrollment Event and ID Assignment record submitted
Person Type	Yes	VarChar(2)	No	The current person type of the individual. 02 – Student 03 – Staff This field is mandatory for every Enrollment Event and ID Assignment record submitted
Reserved Field	No	VarChar(1)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(100)	No	Not used by TEA. Leave this field blank
Entry/Exit Date	Yes/No	date	No	The month, day, and year on which a student enrolls or withdraws from the reporting campus. Valid Formats: • mm/dd/yyyy • m/d/yyyy • mm/d/yyyy • m/dd/yyyy • yyyy-mm-dd This field is mandatory for every Enrollment Event record submitted. This field must be left blank for all ID Assignment records.
Entry/Exit Type	Yes/No	Varchar(2)	No	Indicates if the corresponding date is an enrollment or withdrawal date. 01 – Entry 02 – Exit This field is mandatory for every Enrollment Event record submitted. This field must be left blank for all ID Assignment records.
Reserved Field	No	VarChar(100)	No	Not used by TEA. Leave this field blank
Entry/Exit Verified Flag	Yes/No	Varchar(1)	No	Indicates the status of the enrollment event. 1 – Verified 3 – Calendar 4 – Delete Entry/Exit Date, Entry/Exit Type, are required if this field is provided.
Reserved Field	No	datetime	No	Not used by TEA. Leave this field blank

Field Name	Required	System - Data type	Used for Matching	Notes/Format Details
Reserved Field	No	Numeric (10.2)	No	Not used by TEA. Leave this field blank
Reserved Field	No	Varchar(25)	No	Not used by TEA. Leave this field blank
Reserved Field	No	Varchar(100)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(100)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(100)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(100)	No	Not used by TEA. Leave this field blank
Reserved Field	No	Numeric(4,0)	No	Not used by TEA. Leave this field blank
Reserved Field	No	datetime	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(3)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(255)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(255)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(255)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(12)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(50)	No	Not used by TEA. Leave this field blank
Reserved Field	No	VarChar(10)	No	Not used by TEA. Leave this field blank

The Cancelled Records File contains all the fields in the Detail Record in addition to the following field:

Record Comments	No	VarChar (2048)	No	This field contains a list of validation errors that the application encountered for this input record during the validation process. If more than one error was found in a record, all errors are listed with each one delimited from the other by a semicolon.
-----------------	----	----------------	----	--

NOTE: One batch file should not contain more than 40,000 detail records.

Trailer Record Layout

The trailer record should always be the last record in the file and should contain the following fields:

Field Name	Required	Data Type	Format Details
Record Type	Yes	VarChar (2)	The Record Type Value must equal "TT".
Transmission ID	Yes	VarChar (10)	The Transmission ID is a number utilized by the submitter for auditing as an identifier for the submitter. This ID must match the Transmission ID in the header record.
Number of Records	Yes	VarChar (10)	Number of records in the file, including the "TH" and "TT" records. The value should be left aligned and not have any trailing spaces.

There should be no extra spaces or data after the last column in the Trailer Record.

Example for Race Codes:

Five Race fields are available in the application, but the same value cannot currently be supplied in any of the five fields. For example, if “A” is supplied in the Race field, “A” cannot be supplied in the Race 2, Race 3, Race 4, or Race 5 fields. Additionally, data must be supplied in consecutive order and a race column cannot be skipped. For example, a race code cannot be supplied in the Race 4 field if there is not a value in the Race, Race 2, or Race 3 fields.

Valid Values: I (American Indian Alaska Native), A (Asian), B (Black African American), P (Native Hawaiian Pacific Islander), W (White).

Example	Race	Race 2	Race 3	Race 4	Race 5
Black	B				
Black, Asian	B	A			
Black, Asian, White	B	A	W		
White, Asian	W	A			
White, Black	W	B			
White, Black, Asian, American Indian, Pacific Islander	W	B	A	I	P

Example for Entry/Exit Verified Flag:

These flags are used for LEAs that have duplicate student enrollment to communicate with each other regarding the dates posted for the enrollment and withdrawal events.

Verified means the registrar verified the student was enrolled (and was physically present) or actually withdrew on the posted date.

Calendar means an overlap in enrollment dates is attributable to a difference between the two campus calendars. For instance, one campus begins school after the winter break on Jan 4th, and the other campus begins on Jan. 6th. Campus 1 enrolls a new student on Jan 4th, but the withdrawal from campus 002 is not posted until Jan 6th.

Delete means the event record was deleted. Deleted events continue to display in a student’s Event History with a strike through the font.

Sample File for Student or Staff Submission Purpose = ‘001’, Assignment:

This is a comma delimited, double quote qualified file with a header and a trailer record.

```
TH 05/25/2017 14:00:00 TSTFILE4 3.0 delimiter=0X2C source=SIS qualifier=0X22
"ID","043905005","Norris","Chuck","M","10/01/2002","09","043001","S81010100","B","043905","2017","0",
"001","02",
TT TSTFILE4 3
```

Sample File for Student Enrollment Events Submission Purpose = ‘002’, Enrollment Events:

This is a comma delimited, double quote qualified file with a header and a trailer record.

```
TH 05/25/2017 14:00:00 TSTFILE5 3.0 delimiter=0X2C source=SIS qualifier=0X22
"ID","043905005","Norris","Chuck","M","10/01/2002","09","043001","S81010100","B","5468112175","043905",
"2017","0",
"002","02",
"08/22/2016","01",
TT TSTFILE5 3
```

TSDS UNIQUE ID WEB SERVICES TECHNICAL GUIDE

About This Technical Guide

This technical guide serves as a reference guide for the TSDS Unique ID Web Services for Students and Staff. A Web Service is designed to allow different applications from different sources to communicate with TSDS Unique ID using an XML-based process. These Web Services allow TSDS Unique ID system functionality to be exposed for assigning or retrieving identifiers, requesting a list of near matches, submitting near match decisions, and searching by student /staff or batch.

This document explains in detail the information necessary to utilize the TSDS Unique ID Web Services (Web Services). In this document, you will learn:

- How the TSDS Unique ID Web Services work.
- How to interpret the response information sent back by the TSDS Unique ID Web Service.

Submissions of students and staff through the Web Service are logged as a separate batch type, thus allowing for filtering within the TSDS Unique ID system interface later.

This technical guide includes some notes that are designed to highlight important information.

The following Notes indicators are used:



Note: *This box mentions things that require special attention. The symbol to the left indicates an important note to remember.*

About Web Services

TSDS Unique ID includes four Web Services, including ID Assignment, Near Match List, Near Match Resolution, Search by Batch, and Search By Student/Staff. The first three Web Services existed in prior releases and will function as they did previously. The system includes two file formats for Version 7.x and above. To accommodate the new template, new Web Services have been created for ID Assignment, Near Match Resolution, and Near Match List. These new Web Services are identified with V2 in the service names and object names. For example, the new ID Assignment Web Service is IDAssignmentV2 and the Student object is StudentV2. The existing Web Services have not changed.

The new RESTful Web Services in v10.0 are available for version 3 only. All Service Names and Object Names for RESTful Web Services are identified with V3. For example, the ID Assignment Web Service is IDAssignmentV3 and instead of the Student object, a more generic person object PersonV3 is used.

IDAssignmentV2- Assigning/Retrieving an Identifier

The IDAssignmentV2 Web Services will complete the identifier assignment process and assign an identifier, return a list of near matches, update history information for matching records, and will allow a state identifier to be returned. Upon submission of a request, the Web Service will return an ID Assignment Result element. It will be named IDAssignmentResultV2 depending on the service being called. This contains the status property that identifies success values for the request.

If the submission record does not have a matching record in TSDS Unique ID system, the ID Assignment Result element will return a no match status and will assign an ID. The newly assigned ID will be returned in the StateStudentId element.

Example:

```
<stateStudentId xsi:type="xsd:string">5202763107</stateStudentId>
```

If a matching record is found in the system, the history information for the record will be updated if needed as appropriate and will return a status message indicating the history update. If a matching record is found in the system, but the no updates were needed, a status will be returned indicating no update was needed. If the submission record cannot be uniquely identified by the system, the Web Service will return the potential match records for the submission. For more details, please refer to the IDAssignmentResultV2 Status table below and the SOAP Examples in Appendix A.

Web service accounts for LEAs are managed in the TEAL secure environment. These service account credentials are passed in the web service call as parameters.

Process Flow Example†

1. User is working in a system outside of TSDS Unique ID system to submit student data to the state.
2. User gets an error in the other application stating that a student does not have an identifier.
3. User requests an identifier from TSDS Unique ID directly from that other system by using that applications functionality.
4. Other system uses IDAssignmentV2 Web Service to request an identifier from TSDS Unique ID for Students.
5. TSDS Unique ID processes the request, stores the student information in the database, and returns the new or pre-existing identifier to the originating application.

† Indicates that the example provided is only one example of a possible scenario. Other scenarios may exist that could demonstrate the flow process for the web service.

Operations

assignId

The assignId operation of the IDAssignmentV2 services will assign an identifier or return potential matches for a submission, as well as update data as necessary.

Input Elements

- ❖ **STUDENT**-This element will represent the student details for the identifier assignment request. This will be Student or StudentV2 depending on the Web Service used. The student input elements are:

Field/Element	Description	Notes
SSN	<p>Required. <i>Valid Values/Format:</i> Must be 9 digits, can include “-” but must be formatted correctly with three, two and four digits.</p> <p><i>Example:</i> 444335555 OR 444-33-5555</p> <p>Or 8 digits with the character “S” in front. Example S44335555</p>	V1, V2 and V3
birthDate	<p>Required. <i>Valid Values/Format:</i> yyyy-mm-dd; MM/DD/YYYY;</p> <p><i>Example:</i> 2000-10-30</p>	V1, V2 and V3
districtCode	<p>Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and location.</p>	V1, V2 and V3
locationCode	<p>Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and location.</p>	V3 only
gender	<p>Required. <i>Valid Values/Format:</i> F or M</p>	V1, V2 and V3
gradeLevel	<p>Required. <i>Valid Values/Format:</i> EE (Early Education), PK (Pre-Kindergarten), KG (Kindergarten), 01 (Grade 1), 02 (Grade 2), 03 (Grade 3), 04 (Grade 4), 05 (Grade 5), 06 (Grade 6), 07 (Grade 7), 08 (Grade 8), 09 (Grade 9), 10 (Grade 10), 11 (Grade 11), 12 (Grade 12), and 00 (only valid for Staff).</p>	V1, V2 and V3
classification	<p>Required. <i>Valid Values/Format:</i> length must be less than or equal to 20 characters.</p>	V3 only
localStudentId	<p>Required. <i>Valid Values/Format:</i> Length must be less than or equal to 20 characters. <i>Example:</i> 4857390022</p>	V1, V2 and V3
localPersonId	<p>Required. <i>Valid Values/Format:</i> Length must be less than or equal to 20 characters. <i>Example:</i> 4857390</p>	V3 only

Field/Element	Description	Notes
<i>raceEthnicCode</i>	Required. <i>Valid Values/Format:</i> I A B P W	V1, V2 and V3
<i>residentDistrictCode</i>	Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and location.	V1, V2 and V3
<i>residentLocationCode</i>	Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and location.	V3 only
<i>schoolCode</i>	Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and district.	V1, V2 and V3
<i>buildingCode</i>	Required. <i>Valid Values/Format:</i> Must be valid based on user authentication and district.	V3 only
<i>schoolYear</i>	Required. <i>Valid Values/Format:</i> Must be any 4-digit number, cannot start with 0. <i>Example:</i> 2008	V1, V2 and V3
<i>enrollmentYear</i>	Required. <i>Valid Values/Format:</i> Must be any 4-digit number, cannot start with 0. <i>Example:</i> 2008	V3 only
<i>stateStudentId</i>	Optional. <i>Valid Values/Format:</i> Must be numeric with a length of 10 or 12 characters.	V1, V2 and V3
<i>statePersonId</i>	Optional. <i>Valid Values/Format:</i> Must be numeric with a length of 10 or 12 characters.	V3 only
<i>studentFirstName</i>	Required. <i>Valid Values/Format:</i> Length must be less than or equal to 60 characters.	V1, V2 and V3
<i>firstName</i>	Required. <i>Valid Values/Format:</i> Length must be less than or equal to 60 characters.	V3 only
<i>studentLastName</i>	Required. <i>Valid Values/Format:</i> Length must be less than or equal to 60 characters.	V1, V2 and V3

Field/Element	Description	Notes
<i>studentMiddleName</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V1, V2 and V3
<i>middleName</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only
<i>studentSuffix</i>	Optional. <u>Valid Values/Format:</u> 1 (Jr), 2 (Sr), 3 (II), 4 (III), 5 (IV), 6 (V), 7 (VI), 8 (VII), 9 (VIII), A (I), B (IX), C (X)	V1, V2 and V3
<i>nameSuffix</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>alternateID</i>	Optional. <u>Valid Values/Format:</u> Must be numeric with a length of 50 characters. Note- This field is required if the alternateSource is submitted.	V2 only
<i>alternateSource</i>	Optional <u>Valid Values/Format:</u> Must be numeric with a length of 60 characters. Note: This field is required if the alternateID is submitted.	V2 only
<i>previousLastName</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V2 only
<i>sourceSISCode</i>	Required <u>Valid Values/Format:</u> HR or SIS.	V2 only
<i>sourceCode</i>	Required <u>Valid Values/Format:</u> Must validate to the available sources defined in the system.	V3 only

Field/Element	Description	Notes
<i>cdfValuesArray</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters. Note- CDFs are not overwritten if subsequent submissions are blank. To overwrite CDFs NULL must be sent as the value.	V2 and V3
<i>cdfNumberArray</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters. To be used to identify the CDF number associated to the <i>cdfValuesArray</i> values passed. For example, if 3 CDF values are being passed, the <i>cdfNumberArray</i> should indicate which value should be assigned to the specific CDF numbers. CDFs range from 1 to 8.	V2 and V3
<i>ethnicityIndicator</i>	Required. <u>Valid Values/Format:</u> 0 or 1.	V2 and V3
<i>Race2Code</i>	Optional. <u>Valid Values/Format:</u> I A B P W.	V2 and V3
<i>Race3Code</i>	Optional. <u>Valid Values/Format:</u> I A B P W.	V2 and V3
<i>Race4Code</i>	Optional. <u>Valid Values/Format:</u> I A B P W.	V2 and V3
<i>Race5Code</i>	Optional. <u>Valid Values/Format:</u> I A B P W.	V2 and V3
<i>ethnicSubGroup</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>fullName</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>nickName</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only
<i>birthLocation</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 50 characters.	V3 only
<i>address1</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 50 characters.	V3 only
<i>address2</i>	Optional.	V3 only

Valid Values/Format: Length must be less than or equal to 30 characters.

Field/Element	Description	Notes
<i>city</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 30 characters.	V3 only
<i>state</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters.	V3 only
<i>zip</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 17 characters.	V3 only
<i>geocode</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 30 characters.	V3 only
<i>residencyStatus</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>residencyExpirationDate</i>	Optional. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V3 only
<i>highestDegree</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>degreeProvider</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 125 characters.	V3 only
<i>certificateNumber</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters.	V3 only
<i>certificateType</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters.	V3 only
<i>itinerantFlag</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters	V3 only
<i>submissionPurpose</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 3 characters.	V3 only
<i>personType</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 3 characters.	V3 only
<i>activeFlag</i>	Optional. <u>Valid Values/Format:</u> Length must be equal to 1 character.	V3 only

<i>sourceRefreshDate</i>	Optional. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; <u>Example:</u> 2000-10-30	V3 only
<i>enrollmentStatus</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
Field/Element	Description	Notes
<i>entryExitDate</i>	Optional <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; <u>Example:</u> 2000-10-30	V3 only
<i>entryExitType</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters.	V3 only
<i>salary</i>	Optional. <u>Valid Values/Format:</u> Number with up to 2 decimal values.	V3 only
<i>hireDate</i>	Optional. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; <u>Example:</u> 2000-10-30	V3 only
<i>jobClassCode</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters.	V3 only
<i>jobAssignmentCodePrimary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>jobAssignmentCodeSecondary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>jobAssignmentCodeTertiary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>locationComment</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only

- ❖ **USER ID - Required.** This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
- ❖ **USER PASSWORD - Required.** This value will be the user ID's password that performed the action. Must be a Super User account.

Output Elements

Upon completion of the request, the *IDAssignmentResultV2 element* is returned. This will be IDAssignmentResultV2 depending on the service called. The IDAssignmentResultV2 output will have the following elements in it:

- ❖ *Status* – this is a string containing the status of the function call. For a full list of status values refer to the IDAssignmentV2 Status Table below.
- ❖ *StateStudentId* – use this property to get the state id assigned to the student.
- ❖ *StatePersonId* – (V3 only) use this property to get the state id assigned to the person
- ❖ *SubmissionId* – use this property to get the submission id assigned to the transaction.
- ❖ *BatchNumber* – use this property to get the batch number assigned to the transaction.
- ❖ *cdfMap* – used internally for CDFs.
- ❖ *aliasId* – this property returns the alias ID for the record.
- ❖ *PotentialNearMatches* – this property will return an array of PotentialMatch elements. The data that is returned in this array is for the near matching (master) records. Each near match element will have the following properties:
 - a. STATE STUDENT ID (stateStudentID) – string with the state student Identifier of the matched record.
 - b. LAST NAME (lastName) – the last name of the matched record.
 - c. FIRST NAME (firstName) – the first name of the matched record.
 - d. MIDDLE NAME (middleName) – the middle name of the matched record.
 - e. SUFFIX (suffixName) – the suffix of the matched record.
 - f. GENDER (gender) – the gender code of the matched record.
 - g. DATE OF BIRTH (dob) – the date of birth of the matched record.
 - h. ETHNIC CODE (ethnicCode) – the ethnic code of the matched record.
 - i. SOCIAL SECURITY NUMBER (ssn) – the social security number of the matched record.
 - j. MATCH PROBABILITY (matchProbability) – the match score ranges from Lower Near Match Threshold to Upper Near Match Threshold setting from System Properties.
 - k. COMMENTS (comments) – the comments for the matched record.
 - l. CREATION DATE (createDate) – the date the record was created.
 - m. CLAIM REQUIRED (claimRequired) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
 - n. DISTRICT CODE (districtCode) – the District Code of the matched record.
 - o. SCHOOL CODE (schoolCode) – the School Code of the matched record.
 - p. SCHOOL YEAR (schoolYear) – the school year of the matched record.
 - q. GRADE LEVEL (gradeLevel) – the grade level of the matched record.
 - r. CDF NUMBERS ARRAY (cdfNumbersArray) – the array of CDF by number (V2 only)

-
- s. CDF VALUES ARRAY (cdfValuesArray) – the array of CDF values (V2 only)
 - t. CDF REF NUMBER (cdfRefNumber) (V2 only) – the internal reference to the CDF.
 - u. ALIAS ID (aliasID) (V2 only) – the alias ID of the matched record.
 - v. ALTERNATE SOURCE (alternateSource) (V2 only) – the alternate source of the matched record.

 - w. PREVIOUS LAST NAME (previousLastName) (V2 only) – the previous last name of the matched record.
 - x. SOURCE SIS CODE (sourceSISCode) (V2 only) – the source system of the matched record.
 - y. ETHNICITY INDICATOR (ethnicityIndicator) (V2 only) – the ethnic code for the matched record.
 - z. RACE 2 CODE (Race2Code) (V2 only) – the race 2 code value for the matched record.
 - aa. RACE 2 CODE Description (Race2CodeDesc) (V2 only) – the race 2 code value description for the matched record.
 - bb. RACE 3 CODE (Race3Code) (V2 only) – the race 3 code value for the matched record.
 - cc. RACE 3 CODE Description (Race3CodeDesc) (V2 only) – the race 3 code value description for the matched record.
 - dd. RACE 4 CODE (Race4Code) (V2 only) – the race 4 code value for the matched record.
 - ee. RACE 4 CODE Description (Race4CodeDesc) (V2 only) – the race 4 code value description for the matched record.
 - ff. RACE 5 CODE (Race5Code) (V2 only) – the race 5 code value for the matched record.
 - gg. RACE 5 CODE DESCRIPTION (Race2CodeDesc) (V2 only) – the race 5 code value description for the matched record

Each near match element in V3 will have the following properties:

- a. COMMENTS (comments) – the comments for the matched record.
- b. LAST NAME (lastName) – the last name of the matched record.
- c. CREATION DATE (creationDate) - the creation date of the matched record.
- d. LOCATION CODE (locationCode) - the location code of the matched record.
- e. DATE OF BIRTH (dob) - the date of birth of the matched record.
- f. ETHNIC CODE (ethnicCode) - the ethnic code of the matched record.
- g. FIRST NAME (firstName) - the first name of the matched record.
- h. GENDER (gender) - the gender of the matched record.
- i. CLASSIFICATION (classification) - the classification of the matched record.
- j. LAST NAME (lastName) - the last name of the matched record.
- k. MATCH PROBABILITY (matchProbability) - the match probability of the matched record.
- l. MIDDLE NAME (middleName) - the middle name of the matched record.
- m. RELATION TYPE (relationType) - the relation type of the matched record.
- n. BUILDING CODE (buildingCode) - the building code of the matched record.
- o. RESIDENT LOCATION CODE (residentLocationCode) - the residentLocationCode of the matched record.
- p. SSN (ssn) - the ssn of the matched record.
- q. STATE PERSON ID (statePersonID) - the state person ID of the matched record.

-
- r. NAME SUFFIX (nameSuffix) - the nameSuffix of the matched record.
 - s. CLAIM REQUIRED (claimRequired) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
 - t. ENROLLMENT YEAR (enrollmentYear) - the enrollment year of the matched record.
 - u. PREVIOUS LAST NAME (previousLastName) - the previousLastName of the matched record.
 - v. SOURCE CODE (sourceCode) - the source code of the matched record.
 - w. ALIAS ID (aliasId) - the alias Id of the matched record.
 - x. ALTERNATE SOURCE (alternateSource) - the alternate source of the matched record.
 - y. ALTERNATE ID (alternateID) - the alternate ID of the matched record.
 - z. CDF REF NUMBER (cdfRefNumber) - the internal reference to the CDF.
 - aa. CDF VALUES ARRAY (cdfValuesArray) – array of CDF values of the matched record.
 - bb. CDF NUMBERS ARRAY (cdfNumbersArray) - the array of CDF by number.
 - cc. ETHNICITYINDICATOR (ethnicityIndicator) - the ethnicityIndicator of the matched record.
 - dd. RACE2CODE (race2Code) - the race2Code of the matched record.
 - ee. RACE3CODE (race3Code) - the race3Code of the matched record.
 - ff. RACE4CODE (race4Code) - the race4Code of the matched record.
 - gg. RACE5CODE (race5Code) - the race5Code of the matched record.
 - hh. ETHNICITY INDICATOR DESC (ethnicityIndicatorDesc) - the descripton of ethnicity indicator of the matched record.
 - ii. ETHNIC CODE DESC (ethnicCodeDesc) - the descripton of the race code of the matched record.
 - jj. RACE2 CODE DESC (race2CodeDesc) - the descripton of the race 2 code of the matched record.
 - kk. RACE3 CODE DESC (race3CodeDesc) - the descripton of the race 3 code of the matched record.
 - ll. RACE4 CODE DESC (race4CodeDesc) - the descripton of the race 4 code of the matched record.
 - mm. RACE5 CODE DESC (race5CodeDesc) - the descripton of the race 5 code of the matched record.
 - nn. ETHNIC SUB GROUP (ethnicSubGroup) - the ethnic sub group of the matched record.
 - oo. MOTHERS MAIDEN NAME (mothersMaidenName) - the mothers maiden name of the matched record.
 - pp. FULLNAME (fullName) - the full name of the matched record.
 - qq. NICK NAME (nickName) - the nick name of the matched record.
 - rr. BIRTH LOCATION (birthLocation) - the birth location of the matched record.
 - ss. ADDRESS1 (address1) - the address 1 of the matched record.
 - tt. ADDRESS2 (address2) - the address 2 of the matched record.
 - uu. CITY (city) - the city of the matched record.
 - vv. STATE (state) - the state of the matched record.
 - ww. ZIP (zip) - the zip of the matched record.
 - xx. GEOCODE (geocode) - the geocode of the matched record.
 - yy. RESIDENCY STATUS (residencyStatus) - the residency status of the matched record.
 - zz. RESIDENCY EXPIRATION DATE (residencyExpirationDate) - the residency expiration date of the matched record.
 - aaa. HIGHEST DEGREE (highestDegree) - the highest degree of the matched record.
-

-
- bbb. SUBJECT MATTER AREA (*subjectMatterArea*) - the subject/matter area of the matched record.
 - ccc. DEGREE PROVIDER (*degreeProvider*) - the degree provider of the matched record.
 - ddd. CERTIFICATE NUMBER (*certificateNumber*) - the certificate number of the matched record.
 - eee. CERTIFICATE TYPE (*certificateType*) - the certificate type of the matched record.
 - fff. ITINERANT FLAG (*itinerantFlag*) - the itinerant flag of the matched record.
 - ggg. SUBMISSION PURPOSE (*submissionPurpose*) - the submission purpose of the matched record.
 - hhh. PERSON TYPE (*personType*) - the person type of the matched record.
 - iii. ACTIVE FLAG (*activeFlag*) - the active flag of the matched record.
 - jjj. SOURCE REFRESH DATE (*sourceRefreshDate*) - the source refresh date of the matched record.
 - kkk. MULTIPLE ACTIVE ENROLLMENT COUNT (*multipleActiveEnCount*) - the *multipleActiveEnCount* of the matched record.
 - III. ENROLLMENT STATUS (*enrollmentStatus*) - the enrollment status of the matched record.
 - mmm. ENTRY EXIT DATE (*entryExitDate*) - the entry/exit date of the matched record.
 - nnn. ENTRY EXIT TYPE (*entryExitType*) - the entry/exit type of the matched record.
 - ooo. ENTRY EXIT CODE (*entryExitCode*) - the entry/exit code of the matched record.
 - ppp. ENTRY EXIT VERIFIED FLAG (*entryExitVerifiedFlag*) - the entry/exit verified flag of the matched record.
 - qqq. SALARY (*salary*) - the salary of the matched record.
 - rrr. HIRE DATE (*hireDate*) - the hire date of the matched record.
 - sss. JOB CLASS CODE (*jobClassCode*) - the job class code of the matched record.
 - ttt. JOBASSIGNMENTCODEPRIMARY (*jobAssignmentCodePrimary*) – the primary job assignment code of the matched record.
 - uuu. JOBASSIGNMENTCODESECONDARY (*jobAssignmentCodeSecondary*) - the secondary job assignment code of the matched record.
 - vvv. JOB ASSIGNMENT CODE TERTIARY (*jobAssignmentCodeTertiary*) - the tertiary job assignment code of the matched record.
 - www. LOCATIONCOMMENT (*locationComment*) - the location comments for the matched record.
 - xxx. LOCATION PROCESS STATUS (*locationProcessStatus*) - the *locationProcessStatus* of the matched record.
 - yyy. EVENT PROCESS STATUS (*eventProcessStatus*) - the *eventProcessStatus* of the matched record.
- ❖ *fieldsWithErrors* –returns an array of field errors. The possible messages are:
- a. LAST_NAME – the submitted value was too long or null.
 - b. FIRST_NAME – the submitted value was too long or null.
 - c. MIDDLE_NAME – the submitted value was too long.
 - d. SUFFIX – the submitted value was too long.
 - e. GENDER – the submitted value was too long, invalid, or null.
 - f. DATE_OF_BIRTH – the submitted value was too long, invalid, or null.
 - g. ETHNICITY– the submitted value was too long or invalid.
 - h. SSN – the submitted value was invalid.
-

- i. GRADE_LEVEL - the submitted value was too long, invalid, or null.
- j. LOCAL_STUDENT_ID – the submitted value was too long, invalid, or null.
- k. SCHOOL_YEAR – the submitted value was too long, invalid, or null.
- l. DISTRICT_CODE – the submitted value was too long, invalid, or null.
- m. SCHOOL_CODE – the submitted value was too long, invalid, or null.
- n. RES_DISTRICT_CODE – the submitted value was too long, invalid, or null.
- o. STATE_STUDENT_ID – the submitted value was too long or invalid.
- p. SOURCE_SYSTEM– the submitted value was too long or invalid. (V2only)
- q. ALTERNATE_SOURCE– the submitted value was too long or invalid. (V2 only)
- r. ALTERNATE_ID – the submitted value was too long or invalid. (V2 only)
- s. ALTERNATE_LAST_NAME - the submitted value was too long. (V2 only)
- t. CDF_XXXXX – the submitted value was too long (V2 only). XXXXX stands for the name of the CDF field.
- u. AGENCY_NOT_FOUND – the submitted value was invalid.
- v. AGENCY_NOT_AUTHORIZED – the user is not authorized to access this agency
- w. ETHNICITY/RACE: INVALID – the submitted value was invalid.
- x. ETHNICITY/RACE: INVALID, REQUIRED – the value was not submitted.
- y. ETHNICITY/RACE: DISABLED – a value was not expected.
- z. RACE2_CODE – the submitted value was invalid.
- aa. RACE3_CODE – the submitted value was invalid.
- bb. RACE4_CODE – the submitted value was invalid.
- cc. RACE5_CODE – the submitted value was invalid.
- dd. RACE2_CODE: DISABLED – the submitted value was not expected.
- ee. RACE3_CODE: DISABLED – the submitted value was not expected.
- ff. RACE4_CODE: DISABLED – the submitted value was not expected.
- gg. RACE5_CODE: DISABLED – the submitted value was not expected.
- hh. ETHNIC_SUB_GROUP – the submitted value was invalid.
- ii. MOTHERS_MAIDEN_NAME – the submitted value was invalid.
- jj. FULL_NAME – the submitted value was invalid.
- kk. NICKNAME – the submitted value was invalid.
- ll. BIRTH_LOCATION – the submitted value was invalid.
- mm. ADDRESS_1 – the submitted value was invalid.
- nn. ADDRESS_2 – the submitted value was invalid.
- oo. CITY – the submitted value was invalid.
- pp. STATE – the submitted value was invalid.
- qq. ZIP – the submitted value was invalid.
- rr. GEOCODE – the submitted value was invalid.

- ss. RESIDENCY_STATUS – the submitted value was invalid.
- tt. RESIDENCY_EXPIRATION – the submitted value was invalid.
- uu. HIGHEST_DEGREE – the submitted value was invalid.
- vv. SUBJECT_MATTER_AREA – the submitted value was invalid.
- ww. DEGREE_PROVIDER – the submitted value was invalid.
- xx. CERTIFICATE_NUMBER – the submitted value was invalid.
- yy. CERTIFICATE_TYPE – the submitted value was invalid.
- zz. ITINERANT_FLAG – the submitted value was invalid.
- aaa. SUBMISSION_PURPOSE – the submitted value was invalid.
- bbb. PERSON_TYPE – the submitted value was invalid.
- ccc. ACTIVE_FLAG – the submitted value was invalid.
- ddd. ENROLLMENT_STATUS – the submitted value was invalid.
- eee. ENTRY_EXIT_DATE – the submitted value was invalid.
- fff. ENTRY_EXIT_TYPE – the submitted value was invalid.
- ggg. ENTRY_EXIT_CODE – the submitted value was invalid.
- hhh. ENTRY_EXIT_VERIFIED_FLAG – the submitted value was invalid.
- iii. SALARY – the submitted value was invalid.
- jjj. HIRE_DATE – the submitted value was invalid.
- kkk. JOB_CLASS_CODE – the submitted value was invalid.
- lll. JOB_ASSIGNMENT_CODE_PRIMARY – the submitted value was invalid.
- mmm. JOB_ASSIGNMENT_CODE_SECONDARY – the submitted value was invalid.
- nnn. JOB_ASSIGNMENT_CODE_TERTIARY – the submitted value was invalid.
- ooo. JOB_ASSIGNMENT_CODE: JOB ASSIGNMENT GAP EXISTS
- ppp. JOB_ASSIGNMENT_CODE: DUPLICATE JOB ASSIGNMENTS
- qqq. LOCATION_COMMENT – the submitted value was invalid.
- rrr. SOURCE_REFRESH_DATE – the submitted value was invalid.
- sss. ETHNICITY: MULTIPLE SAME RACE EXISTS
- ttt. ETHNICITY: RACE GAP EXISTS
- uuu. ETHNICITY_INDICATOR: INVALID – the submitted value was invalid.
- vvv. ETHNICITY_INDICATOR: INVALID FOR GRADE – the submitted value was invalid for the grade
- www. ETHNICITY_INDICATOR: DISABLED – the submitted value was not expected.

Reference WSDL

<https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2?WSDL>

Shown in Appendix B

Example: <https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2?WSDL>

IDAssignmentV2 Transaction Status Table

Status Code/Message	Description	Notes
01	Ready to Validate Data	V1, V2, V3
02	Ready to Assign IDs	V1, V2, V3
03	Ready to Fix Data Errors	V1, V2, V3
04	Canceled During Fix Errors Stage	V1, V2, V3
05	If this value is returned, then the student identifier can be retrieved via the StateStudentId operation. New ID Assigned - No Matching Record Found	V1, V2, V3
06	Ready to Resolve Near Matches/Duplicates If this value is returned the system was not able to assign an identifier. The Web Service will return the list of the potential matches that can be retrieved via the PotentialNearMatches operation.	V1, V2, V3
07	New ID Assigned During Match Resolution Stage	V1, V2, V3
08	Student Found and History Created During Match Resolution Stage	V1, V2, V3
09	Canceled During Match Resolution Stage	V1, V2, V3
10	No Information Available -ID Retired	V1, V2, V3
11	Student Found and History Created -Exact Match If this value is returned the system found a match and updated the system. The state student identifier can be retrieved via the StateStudentId operation.	V1, V2, V3
12	Student Found but No Change in Data -Exact Match If this value is returned the system found a match but there were no updates needed in the system. The state student identifier can be retrieved via the StateStudentId operation.	V1, V2, V3
13	Canceled During Data Validation Stage - ID Contained in Record Not Found in System	V1, V2, V3
14	Ready to Assign IDs -Exact Match	V1, V2, V3
15	Waiting for Claim Response -Auto Claim Created	V1, V2, V3
16	ID Updated and History Created -Auto Claim Created and Accepted	V1, V2, V3
17	ID Not Updated -Auto Claim Created but Disputed	V1, V2, V3
18	Canceled During Assign ID Stage -Claim Required	V1, V2, V3
19	Canceled During Data Validation Stage	V1, V2, V3
20	Canceled During Assign ID Stage	V1, V2, V3

Status Code/Message	Description	Notes
21	Ready to Assign IDs -ID Present in Record -No Exact Match	V1, V2, V3
22	Ready to Assign IDs -Possible Claim	V1, V2, V3
23	Canceled During Assign ID Stage -Claim Already Exists	V1, V2, V3
24	ID Not Updated -Auto Claim Created but Deleted	V1, V2, V3
25	Canceled During Claim Creation	V1, V2, V3
26	Student Found During Assign ID Stage but History Not Created	V1, V2, V3
27	Student Found During Match Resolution Stage but History Not Created	V1, V2, V3
28	New ID Assigned -Administrator	V1, V2, V3
29	Ready to Validate Data -Search	V1, V2, V3
30	Ready to Search IDs	V1, V2, V3
31	Canceled During Fix Errors Stage -Search	V1, V2, V3
32	No Matching Record Found -Search	V1, V2, V3
33	Canceled During ID Search Stage -Multiple Records Found	V1, V2, V3
34	Matching Record Found -Search	V1, V2, V3
35	Canceled During Data Validation Stage -Search	V1, V2, V3
36	Canceled During ID Search Stage -Near Match(es) Found	V1, V2, V3
37	Ready to Fix Data Errors -Search	V1, V2, V3
38	Ready to Assign IDs -Possible Claim Found During Assign ID Stag	V1, V2, V3
39	ID Updated -Administrator	V1, V2, V3
40	Student Found and History Created During Assign ID Stage	V1, V2, V3
41	Student Updated and History Created -Direct Edit	V1, V2, V3
42	Canceled During Data Validation Stage -Claim Required	V1, V2, V3
43	Existing ID Assigned During Match Resolution Stage -No Exact Match	V2 ONLY
44	New ID Created During Match Resolution Stage -No Exact Match	V2 ONLY
FAILED_USER_NOT_FOUND_OR_INACTIVE	The call failed because the user id passed was not found in the system or the user id is not active.	V1, V2, V3
FAILED_VALIDATION	One or more fields have a validation error. Use the fieldsWithErrors array to get a list of the fields.	V1, V2, V3

FAILED_USER_NOT_FOUND	The call failed because the user id was null.	V1, V2, V3
ERROR	An exception occurred.	V1, V2, V3
LOCKOUT	When the system is locked out due to an Administrator lockout or forced lockout by a Matching Engine issue, the lockout status will be returned.	V1, V2, V3
FAILED_USER_NOT_AUTHORIZED	The call failed because the user id is not authorized to perform the request.	V1, V2, V3
FAILED_REQUIRED_CDF_MISSING	The call failed because one or more required customer defined fields were not submitted.	V1, V2, V3
SUCCESS_NO_MATCHING_RECORDS	The call was successful but no matches were found.	V1, V2, V3
SUCCESS_MULTIPLE_MATCHING_RECORDS	The call was successful and multiple matches were found.	V1, V2, V3
SUCCESS_SINGLE_MATCH_RECORD	The call was successful and a single match record was found.	V1, V2, V3

NearMatchListV2 - Retrieving Near Match Lists

The Near Match List Web Service will return a list of near matches found by the TSDS Unique ID system for an input record submitted.

The Web Service will have one operation called NearMatchListV2. Upon submission of a request, the Web Service will return a NearMatchListResult element. The NearMatchListResult element will have a status and an array of PotentialMatch elements.

Process Flow Example†

1. User is working in a system outside of TSDS Unique ID to submit student data to the state.
2. User gets an error in the other application stating that a student does not have an identifier.
3. User requests an identifier from TSDS Unique ID directly from that other system by using that applications functionality.
4. Other system uses the IDAssignmentV2 Web Service to request an identifier from TSDS Unique ID.
5. TSDS Unique ID processes the request, finds one or more near matches/matches and returns the list of near matches to the other application.
6. User can view a list of near matches in the other system and resolve or can retrieve the list later.

† Indicates that the example provided is only one example of a possible scenario. Other scenarios may exist that could demonstrate the flow process for the web service.

Operations

getNearMatches

This operation will return potential match records that matched the submission record during the IDAssignmentV2 request.

Input Elements

- ❖ **SUBMISSION IDENTIFIER –Required.** This value will be the identifier that was assigned to submission record during IDAssignmentV2.
- ❖ **USER ID - Required.** This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
- ❖ **USER PASSWORD - Required.** This value will be the user ID's password that performed the action. Must be a Super User account password.

Output Elements

Upon completion of the NearMatchListV2 request, the *NearMatchListResult element* is returned. The *NearMatchListResult* element will have the following properties:

- ❖ **Status** – this is a string containing the status of the function call. For a full list of status values refer to the NearMatchListV2 Status Table below.
- ❖ **Array of PotentialMatchObjects** - Each near match element will have the following properties:
 - a. **STATE STUDENT ID (STATESTUDENTID)** – string with the state student Identifier of the matched record.
 - b. **LAST NAME (LASTNAME)** – the last name of the matched record.
 - c. **FIRST NAME (FIRSTNAME)** – the first name of the matched record.
 - d. **MIDDLE NAME (MIDDLENAME)** – the middle name of the matched record.
 - e. **SUFFIX (SUFFIXNAME)** – the suffix of the matched record.

- f. GENDER (GENDER) – the gender code of the matched record.
- g. DATE OF BIRTH (DOB) – the date of birth of the matched record.
- h. ETHNIC CODE (ETHNICCODE) – the ethnic code of the matched record.
- i. SOCIAL SECURITY NUMBER (SSN) – the social security number of the matched record.
- j. MATCH PROBABILITY (MATCHPROBABILITY) – the match score ranges from Lower Near Match Threshold to Upper Near Match Threshold setting from System Properties.
- k. COMMENTS (COMMENTS) – the comments for the matched record.
- l. CREATION DATE (CREATIONDATE) – the date the record was created.
- m. CLAIM REQUIRED (CLAIMREQUIRED) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
- n. DISTRICT CODE (DISTRICTCODE) – the District Code of the matched record.
- o. SCHOOL CODE (SCHOOLCODE) – the School Code of the matched record.
- p. SCHOOL YEAR (SCHOOLYEAR) – the school year of the matched record.
- q. GRADE LEVEL (GRADELEVEL) – the grade level of the matched record.
- r. CDF NUMBERS ARRAY (cdfNumbersArray) – the array of CDF by number (V2 only)
- s. CDF VALUES ARRAY (cdfValuesArray) – the array of CDF values (V2 only)
- t. CDF REF NUMBER (cdfRefNumber) (V2 only) – the internal reference to the CDF.
- u. ALIAS ID (aliasID) (V2 only) – the alias ID of the matched record.
- v. ALTERNATE SOURCE (alternateSource) (V2 only) – the alternate source of the matched record.
- w. PREVIOUS LAST NAME (previousLastName) (V2 only) – the previous last name of the matched record.
- x. SOURCE SIS CODE (sourceSISCode) (V2 only) – the source system of the matched record.
- y. ETHNICITY INDICATOR (ethnicityIndicator) (V2 only) – the ethnic code for the matched record.
- z. RACE 2 CODE (Race2Code) (V2 only) – the race 2 code value for the matched record.
- aa. RACE 2 CODE Description (Race2CodeDesc) (V2 only) – the race 2 code value description for the matched record.
- bb. RACE 3 CODE (Race3Code) (V2 only) – the race 3 code value for the matched record.
- cc. RACE 3 CODE Description (Race3CodeDesc) (V2 only) – the race 3 code value description for the matched record
- dd. RACE 4 CODE (Race4Code) (V2 only) – the race 4 code value for the matched record.
- ee. RACE 4 CODE Description (Race4CodeDesc) (V2 only) – the race 4 code value description for the matched record.
- ff. RACE 5 CODE (Race5Code) (V2 only) – the race 5 code value for the matched record.
- gg. RACE 5 CODE DESCRIPTION (Race2CodeDesc) (V2 only) – the race 5 code value description for the matched record

Each near match element will have the following properties in NearMatchListResultV3 objects:

- a. STATE PERSON ID (statePersonId) – string with the state Identifier of the matched record.
- b. LAST NAME (lastName) – the last name of the matched record.
- c. FIRST NAME (firstName) – the first name of the matched record.
- d. MIDDLE NAME (middleName) – the middle name of the matched record.
- e. SUFFIX (suffixName) – the suffix of the matched record.
- f. GENDER (gender) – the gender code of the matched record.
- g. DATE OF BIRTH (dob) – the date of birth of the matched record.
- h. ETHNIC CODE (ethnicCode) – the ethnic code of the matched record.
- i. SOCIAL SECURITY NUMBER (ssn) – the social security number of the matched record.
- j. MATCH PROBABILITY (matchProbability) – the match score ranges from Lower Near Match Threshold to Upper Near Match Threshold setting from System Properties.
- k. COMMENTS (comments) – the comments for the matched record.
- l. CREATION DATE (creationDate) – the date the record was created.
- m. CLAIM REQUIRED (claimRequired) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
- n. BUILDING CODE (buildingCode) – the Building Code of the matched record.
- o. LOCATION CODE (locationCode) – the Location Code of the matched record.
- p. RESIDENT LOCATION CODE (residentLocationCode) – the Resident Location Code of the matched record.
- q. ENROLLMENT YEAR (enrollmentYear) – the enrollment year of the matched record.
- r. CLASSIFICATION (classification) – the classification of the matched record.
- s. CDF NUMBERS ARRAY (cdfNumbersArray) – the array of CDF by number
- t. CDF VALUES ARRAY (cdfValuesArray) – the array of CDF values
- u. CDF REF NUMBER (cdfRefNumber) – the internal reference to the CDF.
- v. ALIAS ID (aliasID) – the alias ID of the matched record.
- w. ALTERNATE SOURCE (alternateSource) – the alternate source of the matched record.
- x. PREVIOUS LAST NAME (previousLastName) – the previous last name of the matched record.
- y. SOURCE CODE (sourceCode) – the source system of the matched record.
- z. ETHNICITY INDICATOR (ethnicityIndicator) – the ethnic code for the matched record.
- aa. ETHNICITY INDICATOR DESCRIPTION (ethnicityIndicatorDesc) – the ethnic code value description for the matched record.
- bb. RACE 2 CODE (race2Code) – the race 2 code value for the matched record.
- cc. RACE 2 CODE DESCRIPTION (race2CodeDesc) – the race 2 code value description for the matched record.
- dd. RACE 3 CODE (race3Code) – the race 3 code value for the matched record.
- ee. RACE 3 CODE DESCRIPTION (race3CodeDesc) – the race 3 code value description for the matched record
- ff. RACE 4 CODE (race4Code) – the race 4 code value for the matched record.

- gg. RACE 4 CODE DESCRIPTION (race4CodeDesc) – the race 4 code value description for the matched record.
- hh. RACE 5 CODE (race5Code) – the race 5 code value for the matched record.
- ii. RACE 5 CODE DESCRIPTION (race5CodeDesc) – the race 5 code value description for the matched record

- jj. ETHNIC SUB GROUP (ethnicSubGroup) – the race sub group for the matched record
- kk. MOTHERS MAIDEN NAME (mothersMaidenName) – the mothers maiden name for the matched record

- ll. FULL NAME (fullName) – the full name for the matched record
- mm. NICK NAME (nickname) – the nick name for the matched record
- nn. BIRTH LOCATION (birthLocation) – the birth location for the matched record
- oo. ADDRESS 1(address1) – the address for the matched record
- pp. ADDRESS 2 (address2) – the address 2 for the matched record
- qq. CITY (city) – the city for the matched record
- rr. STATE (state) – the state code for the matched record
- ss. ZIP (zip) – the zip code for the matched record
- tt. GEO CODE (geocode) – the geo code for the matched record
- uu. RESIDENCY STATUS (residencyStatus) – the residency status code for the matched record
- vv. RESIDENCY EXPIRATION DATE (residencyExpirationDate) – the residency expiration date for the matched record

- ww. HIGHEST DEGREE (highestDegree) – the highest degree code for the matched record
- xx. SUBJECT MATTER AREA (subjectMatterArea) – the subject matter code for the matched record
- yy. DEGREE PROVIDER (degreeProvider) – the degree provider for the matched record
- zz. CERTIFICATE NUMBER (certificateNumber) – the certificate number for the matched record
- aaa. CERTIFICATE TYPE (certificateType) – the certificate type for the matched record
- bbb. ITINERANT FLAG (itinerantFlag) – the itinerant flag for the matched record
- ccc. SUBMISSION PURPOSE (submissionPurpose) – the submission purpose for the matched record
- ddd. PERSON TYPE (personType) – the person type for the matched record
- eee. ACTIVE FLAG (activeFlag) – the active flag for the matched record
- fff. SOURCE REFRESH DATE (sourceRefreshDate) – the source refresh date for the matched record
- ggg. MULTIPLE ACTIVE ENROLLMENT COUNT (multipleActiveEnCount) – the active enrollment count for the matched record

- hhh. ENROLLMENT STATUS (enrollmentStatus) – the enrollment status for the matched record
- iii. ENTRY EXIT DATE (entryExitDate) – the entry exit date for the matched record
- jjj. ENTRY EXIT TYPE (entryExitType) – the entry exit type for the matched record
- kkk. ENTRY EXIT CODE (entryExitCode) – the entry exit code for the matched record

- III. ENTRY EXIT VERIFIED FLAG (entryExitVerifiedFlag) – the entry exit verified flag for the matched record

- mmm. SALARY (salary) – the salary for the matched record
- nnn. HIRE DATE (hireDate) – the hire date for the matched record
- ooo. JOB CLASS CODE (jobClassCode) – the job class code for the matched record
- ppp. JOB ASSIGNMENT PRIMARY (jobAssignmentCodePrimary) – the job assignment code for the matched record
- qqq. JOB ASSIGNMENT CODE SECONDARY (jobAssignmentCodeSecondary) – the job assignment code for the matched record
- rrr. JOB ASSIGNMENT CODE TERTIARY (jobAssignmentCodeTertiary) – the job assignment code for the matched record
- sss. LOCATION COMMENT (locationComment) – the location comment for the matched record
- ttt. LOCATION PROCESS STATUS (locationProcessStatus) – the location process status for the matched record
- uuu. EVENT PROCESS STATUS (eventProcessStatus) – the event process status for the matched record

Reference WSDL

<https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2?WSDL>

Shown in Appendix B.

Example: <https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2?WSDL>

NearMatchListV2 Status Table

Status Code	Description
ERROR	An exception occurred.
FAILED_USER_NOT_FOUND_OR_INACTIVE	The call failed because the user id passed was not found in the system or the user id is not active.
FAILED_STAGE_RECORD_NOT_PENDING_NEAR_MATCH	The submission record is no longer pending the near match status.
FAILED_STAGE_RECORD_NOT_FOUND	The submission record cannot be found in the database.
SUCCESS	The call returned one or more potential match records.
FAILED_USER_NOT_AUTHORIZED	The call failed because the user id was null.
FAILED_INVALID_SUBMISSION_ID	The submission id has an invalid format.

NearMatchResolutionsV2 – Near Match Decisions

The Near Match Resolution Web Service will accept and process a near match decision. The Web Service will perform one of the following actions based on the decision:

1. Cancel – cancel the assignment request.
2. Assign Pre-Existing Identifier – assign an already existing state student identifier to the submission record.
3. Create New ID – create a new state student identifier for the submission record.

Process Flow Example†

1. User is working in a system outside of TSDS Unique ID to submit student data to the state.
2. User gets an error in the other application stating that a student does not have an identifier.
3. User requests an identifier from TSDS Unique ID directly from that other system by using that applications functionality.
4. Other system uses IDAssignmentV2 Web Service to request an identifier from TSDS Unique ID.
5. TSDS Unique ID processes the request, finds one or more near matches/matches and returns the list of near matches to the other application.
6. User is presented with the list of near matches in the other system and makes a decision.
7. Other system uses web services to submit the near match decision.
8. TSDS Unique ID processes and stores the near match decision.

† Indicates that the example provided is only one example of a possible scenario. Other scenarios may exist that could demonstrate the flow process for the web service.

Operations

cancel

This operation will cancel the input record based on the submission id.

Input Elements

- ❖ **SUBMISSION IDENTIFIER - Required.** This value will be the submission identifier that was previously passed back from the IDAssignmentV2 web service.
- ❖ **STATE STUDENT ID** - Should be left blank.
- ❖ **USER IDENTIFIER - Required.** This value will be a string that will identify the user ID that performed the action.
- ❖ **USER PASSWORD - Required.** This value will be a string that will identify the user password that performed the action.

Output Elements

Upon completion of the cancel request, the *NearMatchListResult element* is returned. The *NearMatchListResult element* will have the following properties:

- ❖ **Status** – this is a string containing the status of the function call. For a full list of status values refer to the NearMatchResolutionV2 Status Table below.

assignId

This operation will assign an already existing state student identifier to the input record.

Input Elements

- ❖ **SUBMISSION IDENTIFIER - Required.** This value will be the submission identifier that was previously passed back from the IDAssignmentV2 web service.
- ❖ **STATE STUDENT ID - Required.** The identifier selected to be assigned to the input record.
- ❖ **USER IDENTIFIER - Required.** This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
- ❖ **USER PASSWORD - Required.** This value will be a string that will identify the user password that performed the action. Must be a Super User account password.

Output Elements

Upon completion of the assignment request, the *NearMatchListResult element* is returned. The *NearMatchListResult element* will have the following properties:

- ❖ **Status** – this is a string containing the status of the function call. For a full list of status values refer to the NearMatchResolutionV2 Status Table below.

createNewID

This operation will create a new state student identifier for the input record.

Input Elements

- ❖ **SUBMISSION IDENTIFIER - Required.** This value will be the submission identifier that was previously passed back from the IDAssignmentV2 web service.
- ❖ **STATE STUDENT ID** - Should be left blank.
- ❖ **USER IDENTIFIER - Required.** This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
- ❖ **USER PASSWORD - Required.** This value will be a string that will identify the user password that performed the action. Must be a Super User account password.

Output Elements

Upon completion of the createNewId request, the *NearMatchListResult Object* is returned. The *NearMatchListResult element* will have the following properties:

- ❖ **Status** – this is a string containing the status of the function call. For a full list of status values refer to the NearMatchResolutionV2 Object Status Table below.

- ❖ *StateStudentId* – use this property to get the state id assigned to the student.
- ❖ *AliasID* – use this property to obtain the alias ID.

Reference WSDL

<https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2>

Shown in Appendix B.

Example: <https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2>

NearMatchResolutionV2 Object Status Table

Status Code	Description
ERROR	An exception occurred.
FAILED_USER_NOT_FOUND	The call failed because the user id was null.
FAILED_USER_NOT_FOUND_OR_INACTIVE	The call failed because the user id passed was not found in the system or the user id is not active.
FAILED_STAGE_RECORD_NOT_FOUND	The submission record cannot be found in the database.
FAILED_STAGE_RECORD_NOT_PENDING_NEAR_MATCH	The submission record is no longer pending the near match status.
FAILED_STATE_ID_NOT_FOUND	The state student identifier passed in was not found in the system.
FAILED_INVALID_INPUT_ID	The submission id is invalid.
SUCCESS	The call was successful.

StudentSearch – Searching for a Student / Staff

The Student Search Web Service will return a list of potential matches found by the TSDS Unique ID system for the input record submitted. This Web Service works similarly to the IDAssignmentV2 Web Services, but it does not assign identifiers in any case.

The Web Service will have one operation called searchStudent. Upon submission of a request, the Web Service will return a StudentSearchResult element. This element will have a status and an array of PotentialMatch elements. This array includes a match probability score that can be utilized to determine a match.

Note- records should not be considered matches if they are not higher than the Upper Near Match Threshold configured in the system. Records in a multiple match scenario should be reviewed before being accepted as a match. This Web Service is only functional with TSDS UID System 7 or above.

Operations

searchStudent

This operation will return potential match records that matched the submission record during the search request.

searchWithIDExactMatch

This operation will try to do an exact match with student demographic information when a valid STATE_STUDENT_ID is submitted in the STUDENTINPUT element. If an exact match is found, the result object containing single match record is returned. If exact match fails, result object will contain no matches. It behaves exactly like searchStudent operation when STATE_STUDENT_ID is empty or invalid. Unlike the regular Exact Match Rule, this does not return a list of potential matches. Refer to the STUDENTINPUT and output elements below.

Input Elements

- *STUDENTINPUT*-This element will represent the student to search. The student input elements are:

Field/Element	Description	Notes
alternateld	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 50 characters.	V1, V2, V3
alternateSource	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V1, V2, V3
birthDate	Required. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V1, V2, V3
cdfNumbersArray	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters.	V1, V2, V3

Note-CDFs are not overwritten if subsequent submissions are blank. To overwrite CDFs NULL must be sent as the

cdfValuesArray	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters. To be used to identify the CDF number associated to the cdfValuesArray values passed. For example, if 3 CDF values are being passed, the cdfNumberArray should indicate which value should be assigned to the specific CDF numbers. CDFs range from 1 to 8.	V1, V2, V3
districtCode	Required. <u>Valid Values/Format:</u> Must be valid based on user authentication and location.	V1, V2, V3
locationCode	Required. <u>Valid Values/Format:</u> Must be valid based on user authentication and location.	V3 only
gender	Required. <u>Valid Values/Format:</u> F or M	V1, V2, V3
gradeLevel	Optional. <u>Valid Values/Format:</u> EE (Early Education), PK (Pre-Kindergarten), KG (Kindergarten), 01 (Grade 1), 02 (Grade 2), 03 (Grade 3), 04 (Grade 4), 05 (Grade 5), 06 (Grade 6), 07 (Grade 7), 08 (Grade 8), 09 (Grade 9), 10 (Grade 10), 11 (Grade 11), 12 (Grade 12), and 00 (only valid for Staff)	V1, V2, V3
classification	Required. <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters. <i>Example:</i> 4857390022	V3 only
localStudentId	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters. <i>Example:</i> 4857390022	V1, V2, V3
localPersonid	Required. <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters. <i>Example:</i> 4857390022	V3 only
previousLastName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V1, V2, V3
raceEthnicCode	Optional. <u>Valid Values/Format:</u> I A B P W	V1, V2, V3

residentDistrictCode	Optional. <u>Valid Values/Format:</u> Must be valid based on user authentication and location.	V1, V2, V3
residentLocationCode	Optional. <u>Valid Values/Format:</u> Must be valid based on user authentication and location.	V3 only
schoolCode	Required. <u>Valid Values/Format:</u> Must be valid based on user authentication and district.	V1, V2, V3
buildingCode	Required. <u>Valid Values/Format:</u> Must be valid based on user authentication and district.	V3 only
schoolYear	Optional. <u>Valid Values/Format:</u> Must be any 4-digit number, cannot start with 0.	V1, V2, V3
enrollmentYear	Required. <u>Valid Values/Format:</u> Must be any 4-digit number, cannot start with 0. <i>Example: 2008</i>	V3 only
sourceSISCode	Optional <u>Valid Values/Format:</u> Must validate to the available sources defined in the system.	V1, V2, V3
SSN	Optional. <u>Valid Values/Format:</u> Must be 9 digits, can include "-" but must be formatted correctly with three, two and four digits. <i>Example: 444335555 OR 444-33-5555</i> Or 8 digits with the character "S" in front. Example S44335555	V1, V2, V3
stateStudentId	Optional. <u>Valid Values/Format:</u> Must be numeric with a length of 10 or 12 characters.	V1, V2, V3
statePersonId	Optional. <u>Valid Values/Format:</u> Must be numeric with a length of 10 or 12 characters.	V3 only
studentFirstName	Required. <u>Valid Values/Format:</u> Length must be less than or	V1, V2, V3
firstName	Required. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only

Field/Element	Description	Notes
studentLastName	Required. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V1, V2, V3
lastName	Required. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only
studentMiddleName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V1, V2, V3
middleName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only
studentSuffix	Optional. <u>Valid Values/Format:</u> 1 (Jr), 2 (Sr), 3 (II), 4 (III), 5 (IV), 6 (V), 7 (VI), 8 (VII), 9 (VIII), A (I), B (IX), C (X)	V1, V2, V3
nameSuffix	Optional. <u>Valid Values/Format:</u> 1 (Jr), 2 (Sr), 3 (II), 4 (III), 5 (IV), 6 (V), 7 (VI), 8 (VII), 9 (VIII), A (I), B (IX), C (X)	V3 only
ethnicityIndicator	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 4	V1, V2, V3
Race2Code	Optional <u>Valid Values/Format:</u> I A B P W	V1, V2, V3
Race3Code	Optional <u>Valid Values/Format:</u> I A B P W	V1, V2, V3
Race4Code	Optional <u>Valid Values/Format:</u> I A B P W	V1, V2, V3
Race5Code	Optional <u>Valid Values/Format:</u> I A B P W	V1, V2, V3
ethnicSubGroup	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
mothersMaidenName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only
fullName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
nickName	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 60 characters.	V3 only

Field/Element	Description	Notes
<i>birthLocation</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 50 characters.	V3 only
<i>address1</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 50 characters.	V3 only
<i>address2</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 30 characters.	V3 only
<i>city</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 30 characters.	V3 only
<i>state</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters.	V3 only
<i>zip</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 17 characters.	V3 only
<i>geocode</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 30 characters.	V3 only
<i>residencyStatus</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>residencyExpirationDate</i>	Optional <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V3 only
<i>highestDegree</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>subjectMatterArea</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters.	V3 only
<i>degreeProvider</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 125 characters.	V3 only
<i>certificateNumber</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters.	V3 only

<i>certificateType</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters.	V3 only
<i>itinerantFlag</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters	V3 only
<i>submissionPurpose</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 3 characters.	V3 only
<i>personType</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 3 characters.	V3 only
<i>activeFlag</i>	Optional. <u>Valid Values/Format:</u> Length must be equal to 1 character.	V3 only
<i>sourceRefreshDate</i>	Optional. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V3 only
<i>enrollmentStatus</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 10 characters.	V3 only
<i>entryExitDate</i>	Optional <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V3 only
<i>entryExitType</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 2 characters.	V3 only
<i>entryExitCode</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 20 characters.	V3 only
<i>entryExitVerifiedFlag</i>	Optional <u>Valid Values/Format:</u> Length must be less than or equal to 1 character.	V3 only
<i>salary</i>	Optional. <u>Valid Values/Format:</u> Number with up to 2 decimal values.	V3 only
<i>hireDate</i>	Optional. <u>Valid Values/Format:</u> yyyy-mm-dd; MM/DD/YYYY; Example: 2000-10-30	V3 only
<i>jobClassCode</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 25 characters.	V3 only

<i>jobAssignmentCodePrimary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>jobAssignmentCodeSecondary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>jobAssignmentCodeTertiary</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only
<i>locationComment</i>	Optional. <u>Valid Values/Format:</u> Length must be less than or equal to 100 characters.	V3 only

1. **USER ID - Required.** This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
2. **USER PASSWORD - Required.** This value will be the user ID's password that performed the action. Must be a Super User account password.

Output Elements:

Upon completion of the StudentSearch request, the *StudentSearchResult element* is returned. The *StudentSearchResult* element will have the following properties:

1. *Status* – this is a string containing the status of the function call. For a full list of status values refer to the IDAssignmentV2 Status Table below.
2. *StateStudentId* – use this property to get the state id assigned to the student.
3. *SubmissionId* – use this property to get the submission id assigned to the transaction.
4. *BatchNumber* – use this property to get the batch number assigned to the transaction.
5. *cdfMap* – used internally for CDFs.
6. *aliasId* – this property will return the alias ID.
7. *PotentialNearMatches* – this property will return an array of PotentialMatch elements. The data that is returned in this array is for the near matching (master) records. Each near match element will have the following properties:

- a. STATE STUDENT ID (stateStudentID) – string with the state student Identifier of the matched record.
- b. LAST NAME (lastName) – the last name of the matched record.
- c. FIRST NAME (firstName) – the first name of the matched record.
- d. MIDDLE NAME (middleName) – the middle name of the matched record.
- e. SUFFIX (suffixName) – the suffix of the matched record.
- f. GENDER (gender) – the gender code of the matched record.
- g. DATE OF BIRTH (dob) – the date of birth of the matched record.
- h. ETHNIC CODE (ethnicCode) – the ethnic code of the matched record.
- i. SOCIAL SECURITY NUMBER (ssn) – the social security number of the matched record.
- j. MATCH PROBABILITY (matchProbability) – the match score ranges from Lower Near Match Threshold to Upper Near Match Threshold setting from System Properties.
- k. COMMENTS (comments) – the comments for the matched record.
- l. CREATION DATE (createDate) – the date the record was created.
- m. CLAIM REQUIRED (claimRequired) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
- n. DISTRICT CODE (districtCode) – the District Code of the matched record.
- o. SCHOOL CODE (schoolCode) – the School Code of the matched record.
- p. SCHOOL YEAR (schoolYear) – the school year of the matched record.
- q. GRADE LEVEL (gradeLevel) – the grade level of the matched record.
- r. CDF NUMBERS ARRAY (cdfNumbersArray) – the array of CDF by number (V2 only)
- s. CDF VALUES ARRAY (cdfValuesArray) – the array of CDF values (V2 only)
- t. CDF REF NUMBER (cdfRefNumber) (V2 only) – the internal reference to the CDF.
- u. ALIAS ID (aliasID) (V2 only) – the alias ID of the matched record.
- v. ALTERNATE SOURCE (alternateSource) (V2 only) – the alternate source of the matched record.
- w. PREVIOUS LAST NAME (previousLastName) (V2 only) – the previous last name of the matched record.
- x. SOURCE SIS CODE (sourceSISCode) (V2 only) – the source system of the matched record.
- y. ETHNICITY INDICATOR (ethnicityIndicator) (V2 only) – the ethnic code for the matched record.
- z. RACE 2 CODE (Race2Code) (V2 only) – the race 2 code value for the matched record.
- aa. RACE 2 CODE Description (Race2CodeDesc) (V2 only) – the race 2 code value description for the matched record.
- bb. RACE 3 CODE (Race3Code) (V2 only) – the race 3 code value for the matched record.
- cc. RACE 3 CODE Description (Race3CodeDesc) (V2 only) – the race 3 code value description for the matched record
- dd. RACE 4 CODE (Race4Code) (V2 only) – the race 4 code value for the matched record.
- ee. RACE 4 CODE Description (Race4CodeDesc) (V2 only) – the race 4 code value description for the matched record.
- ff. RACE 5 CODE (Race5Code) (V2 only) – the race 5 code value for the matched record.

gg. RACE 5 CODE DESCRIPTION (Race2CodeDesc) (V2 only) – the race 5 code value description for the matched record

Each near match element will have the following properties in StudentSearchResultV3(V3 only) objects:

- a. STATE PERSON ID (statePersonId) – string with the state Identifier of the matched record.
- b. LAST NAME (lastName) – the last name of the matched record.
- c. FIRST NAME (firstName) – the first name of the matched record.
- d. MIDDLE NAME (middleName) – the middle name of the matched record.
- e. SUFFIX (suffixName) – the suffix of the matched record.
- f. GENDER (gender) – the gender code of the matched record.
- g. DATE OF BIRTH (dob) – the date of birth of the matched record.
- h. ETHNIC CODE (ethnicCode) – the ethnic code of the matched record.
- i. SOCIAL SECURITY NUMBER (ssn) – the social security number of the matched record.
- j. MATCH PROBABILITY (matchProbability) – the match score ranges from Lower Near Match Threshold to Upper Near Match Threshold setting from System Properties.
- k. COMMENTS (comments) – the comments for the matched record.
- l. CREATION DATE (creationDate) – the date the record was created.
- m. CLAIM REQUIRED (claimRequired) – indicates if a claim is required for the record. This can occur when Claiming is enabled.
- n. BUILDING CODE (buildingCode) – the Building Code of the matched record.
- o. LOCATION CODE (locationCode) – the Location Code of the matched record.
- p. RESIDENT LOCATION CODE (residentLocationCode) – the Resident Location Code of the matched record.
- q. ENROLLMENT YEAR (enrollmentYear) – the enrollment year of the matched record.
- r. CLASSIFICATION (classification) – the classification of the matched record.
- s. CDF NUMBERS ARRAY (cdfNumbersArray) – the array of CDF by number
- t. CDF VALUES ARRAY (cdfValuesArray) – the array of CDF values
- u. CDF REF NUMBER (cdfRefNumber) – the internal reference to the CDF.
- v. ALIAS ID (aliasID) – the alias ID of the matched record.
- w. ALTERNATE SOURCE (alternateSource) – the alternate source of the matched record.
- x. PREVIOUS LAST NAME (previousLastName) – the previous last name of the matched record.
- y. SOURCE CODE (sourceCode) – the source system of the matched record.
- z. ETHNICITY INDICATOR (ethnicityIndicator) – the ethnic code for the matched record.
- aa. ETHNICITY INDICATOR DESCRIPTION (ethnicityIndicatorDesc) – the ethnic code value description for the matched record.
- bb. RACE 2 CODE (race2Code) – the race 2 code value for the matched record.
- cc. RACE 2 CODE DESCRIPTION (race2CodeDesc) – the race 2 code value description for the matched record.

- dd. RACE 3 CODE (race3Code) – the race 3 code value for the matched record.
- ee. RACE 3 CODE DESCRIPTION (race3CodeDesc) – the race 3 code value description for the matched record
- ff. RACE 4 CODE (race4Code) – the race 4 code value for the matched record.
- gg. RACE 4 CODE DESCRIPTION (race4CodeDesc) – the race 4 code value description for the matched record.
- hh. RACE 5 CODE (race5Code) – the race 5 code value for the matched record.
- ii. RACE 5 CODE DESCRIPTION (race5CodeDesc) – the race 5 code value description for the matched record
- jj. ETHNIC SUB GROUP (ethnicSubGroup) – the race sub group for the matched record
- kk. MOTHERS MAIDEN NAME (mothersMaidenName) – the mother’s maiden name for the matched record
- ll. FULL NAME (fullName) – the full name for the matched record
- mm. NICK NAME (nickname) – the nick name for the matched record
- nn. BIRTH LOCATION (birthLocation) – the birth location for the matched record
- oo. ADDRESS 1(address1) – the address for the matched record
- pp. ADDRESS 2 (address2) – the address 2 for the matched record
- qq. CITY (city) – the city for the matched record
- rr. STATE (state) – the state code for the matched record
- ss. ZIP (zip) – the zip code for the matched record
- tt. GEO CODE (geocode) – the geo code for the matched record
- uu. RESIDENCY STATUS (residencyStatus) – the residency status code for the matched record
- vv. RESIDENCY EXPIRATION DATE (residencyExpirationDate) – the residency expiration date for the matched record
- ww. HIGHEST DEGREE (highestDegree) – the highest degree code for the matched record
- xx. SUBJECT MATTER AREA (subjectMatterArea) – the subject matter code for the matched record
- yy. DEGREE PROVIDER (degreeProvider) – the degree provider for the matched record
- zz. CERTIFICATE NUMBER (certificateNumber) – the certificate number for the matched record
- aaa. CERTIFICATE TYPE (certificateType) – the certificate type for the matched record
- bbb. ITINERANT FLAG (itinerantFlag) – the itinerant flag for the matched record
- ccc. SUBMISSION PURPOSE (submissionPurpose) – the submission purpose for the matched record
- ddd. PERSON TYPE (personType) – the person type for the matched record
- eee. ACTIVE FLAG (activeFlag) – the active flag for the matched record
- fff. SOURCE REFRESH DATE (sourceRefreshDate) – the source refresh date for the matched record
- ggg. MULTIPLE ACTIVE ENROLLMENT COUNT (multipleActiveEnCount) – the active enrollment count for the matched record
- hhh. ENROLLMENT STATUS (enrollmentStatus) – the enrollment status for the matched record

-
- iii. ENTRY EXIT DATE (`entryExitDate`) – the entry exit date for the matched record
 - jjj. ENTRY EXIT TYPE (`entryExitType`) – the entry exit type for the matched record
 - kkk. ENTRY EXIT CODE (`entryExitCode`) – the entry exit code for the matched record
 - III. ENTRY EXIT VERIFIED FLAG (`entryExitVerifiedFlag`) – the entry exit verified flag for the matched record
 - mmm. SALARY (`salary`) – the salary for the matched record
 - nnn. HIRE DATE (`hireDate`) – the hire date for the matched record
 - ooo. JOB CLASS CODE (`jobClassCode`) – the job class code for the matched record
 - ppp. JOB ASSIGNMENT PRIMARY (`jobAssignmentCodePrimary`) – the job assignment code for the matched record
 - qqq. JOB ASSIGNMENT CODE SECONDARY (`jobAssignmentCodeSecondary`) – the job assignment code for the matched record
 - rrr. JOB ASSIGNMENT CODE TERTIARY (`jobAssignmentCodeTertiary`) – the job assignment code for the matched record
 - sss. LOCATION COMMENT (`locationComment`) – the location comment for the matched record
 - ttt. LOCATION PROCESS STATUS (`locationProcessStatus`) – the location process status for the matched record
 - uuu. EVENT PROCESS STATUS (`eventProcessStatus`) – the event process status for the matched record
- *fieldsWithErrors* – returns an array of field errors. The possible messages are:
 - a. LAST_NAME – the submitted value was too long or null.
 - b. FIRST_NAME – the submitted value was too long or null.
 - c. MIDDLE_NAME – the submitted value was too long.
 - d. SUFFIX – the submitted value was too long.
 - e. GENDER – the submitted value was too long, invalid, or null.
 - f. DATE_OF_BIRTH – the submitted value was too long, invalid, or null.
 - g. ETHNICITY – the submitted value was too long or invalid.
 - h. GRADE_LEVEL - the submitted value was too long, invalid, or null.
 - i. LOCAL_STUDENT_ID – the submitted value was too long, invalid, or null.
 - j. SCHOOL_YEAR – the submitted value was too long, invalid, or null.
 - k. DISTRICT_CODE – the submitted value was too long, invalid, or null.
 - l. SCHOOL_CODE – the submitted value was too long, invalid, or null.
 - m. RES_DISTRICT_CODE – the submitted value was too long, invalid, or null.
 - n. SSN – the submitted value was invalid.
 - o. STATE_STUDENT_ID – the submitted value was too long or invalid.
 - p. SOURCE_SYSTEM – the submitted value was too long or invalid. (V2 only)
 - q. ALTERNATE_SOURCE – the submitted value was too long or invalid. (V2 only)
 - r. ALTERNATE_ID – the submitted value was invalid.

- s. ALTERNATE_LAST_NAME - the submitted value was too long. (V2 only)
- t. CDF_XXXX – the submitted value was too long (V2 only). XXXX stands for the name of the CDF with error.
- u. AGENCY_NOT_FOUND – the submitted value was invalid.
- v. AGENCY_NOT_AUTHORIZED – the user is not authorized to access this agency.

Reference WSDL

<https://tea4avdplbprod.tea.state.tx.us/uid/services/StudentSearch?>

WSDLSShown in Appendix B

Example: <https://tea4avdplbprod.tea.state.tx.us/uid/services/StudentSearch?WSDL>

Search Status Table

Status Code	Description
ERROR	An exception occurred.
FAILED_USER_NOT_FOUND _OR_INACTIVE	The call failed because the user id passed was not found in the system or the user id is not active.
SUCCESS	The call returned one or more potential match records.
FAILED_USER_NOT_FOUND	The call failed because the user id was null.
SUCCESS_MULTIPLE_MATCHING_RECORDS	The call was successful but multiple matches were found.
SUCCESS_SINGLE_MATCH_RECORD	The call was successful and a single match was found.
SUCCESS_NO_MATCHING_RECORDS	The call was successful and no match was found.
FAILED_VALIDATION	The submission failed data validation.
LOCKOUT	The submission failed data validation. When the system is locked out due to an Administrator lockout or forced lockout by a Matching Engine issue, the lockout status will be returned.

BatchInfoSearch – Searching for a Student / Staff

The Batch Info Search Web Service will return batch information for single record batches in TSDS Unique ID system for the input record submitted. TSDS Unique ID Version 7.0 or above is required for this Web Service.

The Web Service will have one operation called `getBatchInformation`. Upon submission of a request, the Web Service will return a `BatchInfoResult` element. This element will have a status and other batch information as described below.

Operations

`getBatchInformation`

This operation will return potential match records that matched the submission record during the search request.

Input Elements

1. *BATCHNUMBER*-This element will represent the batch number to search. It must be a valid number.
2. *USER ID - Required*. This value will be a string that will identify the user ID that performed the action. Must be a Super User account.
3. *USER PASSWORD - Required*. This value will be the user ID's password that performed the action. Must be a Super User account password.

Output Elements:

Upon completion of the `BatchInfo` request, the *BatchInfoResult* element is returned. The *BatchInfoResult* element will have the following properties:

1. *Status* – this is a string containing the status of the function call. For a full list of status values refer to the IDAssignmentV2 Status Table below.
2. *StateStudentId* – use this property to get the state id assigned to the student.
3. *StatePersonId* – use this property to get the state id assigned to the student. (V3 only)
4. *BatchNumber* – use this property to get the batch number assigned to the transaction.
5. *BatchStatus* – use this property to get the batch status for the requested batch. For batch status information, refer to the Batch Status table below.
6. *nearMatchCount* - use this property to get the total number of near match records in the batch.
7. *totalNumberRecords* – use this property to get the total number of records in the batch. This should always equal 1.
8. *transactionStatus* – use this property to get the transaction status of the record. Refer to the numeric values in the "IDAssignmentV2 Transaction Status Table" above.

Batch Statuses

Code	Status/Message
01	FILE UPLOAD COMPLETE
02	LOAD AND VALIDATION COMPLETE
03	ID CREATION STARTED
04	ID CREATION COMPLETE
05	ID CREATION ABORTED
06	ID EXTRACT COMPLETE
07	ARCHIVED TO HISTORY
08	CANCELED
09	INVALID

Code	Status/Message
10	LOAD AND VALIDATION STARTED
11	CLAIM STARTED (NOT USED BY TEA)
12	CLAIM COMPLETE (NOT USED BY TEA)
13	CLAIM CANCELED (NOT USED BY TEA)
14	SEARCH UPLOAD COMPLETE
15	SEARCH VALIDATION STARTED
16	SEARCH VALIDATION ABORTED
17	SEARCH VALIDATION COMPLETED
18	SEARCH STARTED
19	SEARCH ABORTED
20	SEARCH COMPLETED
21	VALIDATION INTERRUPTED
22	ID ASSIGNMENT INTERRUPTED
23	SEARCH VALIDATION INTERRUPTED
24	SEARCH INTERRUPTED
25	SEARCH DATA ERRORS PENDING
26	SEARCH canceled
27	FILE UPLOAD FAILED
28	DATA ERRORS PENDING
29	NEAR MATCHES PENDING

Note-The statuses show above include all possible Batch Statuses in the system. Not all of these will be encountered by Web Services.

Reference WSDL

<https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo?>

WSDL Shown in Appendix B.

Example: <https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo?WSDL>

BatchInfo Search Status Table

Status Code	Description
ERROR	An exception occurred.
FAILED_USER_NOT_FOUND_OR_INACTIVE	The call failed because the user id passed was not found in the system or the user id is not active.
SUCCESS	The call returned one or more potential match records.
FAILED_USER_NOT_FOUND	The call failed because the user id was null.
FAILED_BATCH_NOT_FOUND	The call failed because the batch submitted was not located in the system.
FAILED_BATCH_HAS_MULTIPLE_RECORDS LOCKOUT	The call failed because there are multiple records in the batch submitted. The system only returns single When the system is locked out due to an Administrator lockout or forced lockout by a Matching Engine issue, the lockout status will be returned.
FAILED_NO_TRANSACTION_FOR_BATCH_NOT_FOUND	The call failed because there was no batch matching the Submission batch.
FAILED_BATCH_HAS_NO_RECORDS	The call failed because the submitted batch did not have records.
FAILED_USER_NOT_AUTHORIZED	The call failed because the user was not authorized to submit the Request.

Appendix A – Soap Message Examples

IDAssignmentV2 Request – New ID Example

The sample below demonstrates a SOAP request for a new ID assignment using the IDAssignmentV2 Web Service:

```
<?xml version="1.0" encoding="UTF-8" ?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:q0="http://com.escholar.ws"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <student xsi:type="q0:Student">
        <SSN xsi:type="xsd:string"/>
        <birthDate xsi:type="xsd:string">05/01/1988</birthDate>
        <districtCode xsi:type="xsd:string">123456</districtCode>
        <gender xsi:type="xsd:string">M</gender>
        <gradeLevel xsi:type="xsd:string">10</gradeLevel>
        <localStudentId xsi:type="xsd:string">1113322</localStudentId>
        <raceEthnicCode xsi:type="xsd:string">W</raceEthnicCode>
        <residentDistrictCode xsi:type="xsd:string">0009</residentDistrictCode>
        <schoolCode xsi:type="xsd:string">123456789</schoolCode>
        <schoolYear xsi:type="xsd:string">2007</schoolYear>
        <stateStudentId xsi:type="xsd:string"/>
        <studentFirstName xsi:type="xsd:string">Mira</studentFirstName>
        <studentLastName xsi:type="xsd:string">Rauen</studentLastName>
        <studentMiddleName xsi:type="xsd:string"/>
        <studentSuffix xsi:type="xsd:string"/>
      </student>
      <userId xsi:type="xsd:string">*****</userId>
      <password xsi:type="xsd:string">*****</password>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

IDAssignmentV3 Request – New ID Example

The sample below demonstrates a SOAP request for a new ID assignment using the IDAssignmentV3 Web Service:

```
<?xml version="1.0" encoding="UTF-8" ?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:q0="http://com.escholar.ws"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <student xsi:type="q0:Student">
        <SSN xsi:type="xsd:string"/>
        <birthDate xsi:type="xsd:string">05/01/1988</birthDate>
        <gender xsi:type="xsd:string">M</gender>
        <classification xsi:type="xsd:string">20</gradeLevel>
        <localPersonId xsi:type="xsd:string">1113322</localStudentId>
        <raceEthnicCode xsi:type="xsd:string">W</raceEthnicCode>
      </student>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

```

    <residentLocationCode xsi:type="xsd:string">0009</residentDistrictCode>
    <buildingCode xsi:type="xsd:string">123456789</schoolCode>
    <enrollmentYear xsi:type="xsd:string">2007</schoolYear>
    <statePersonId xsi:type="xsd:string"/>
    <firstName xsi:type="xsd:string">Mira</studentFirstName>
    <lastName xsi:type="xsd:string">Rauen</studentLastName>
    <middleName xsi:type="xsd:string"/>
    <nameSuffix xsi:type="xsd:string"/>
  </student>
  <userId xsi:type="xsd:string">****</userId>
  <password xsi:type="xsd:string">****</password>
</ns0:assignId>
</soapenv:Body>
</soapenv:Envelope>

```

IDAssignmentV2 Response – New ID Example

The sample below demonstrates the SOAP response to the above IDAssignmentV2 submission. The request did not include any data issues and there were no matches, so the response provided the new ID for assignment.

```

<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <assignIdReturn href="#id0"/>
    </ns1:assignIdResponse>
    <multiRef xmlns:ns2="http://com.escholar.ws"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0"
      soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:IDAssignmentResultV2">
      <batchNumber xsi:type="xsd:string">266</batchNumber>
      <fieldsWithErrors xsi:nil="true" xsi:type="soapenc:Array"/>
      <potentialNearMatches xmlns:ns3="http://www.escholar.com"
        xsi:nil="true" xsi:type="ns3:NearMatchArray"/>
      <stateStudentId xsi:type="xsd:string">5202763107</stateStudentId>
      <status xsi:type="xsd:string">05</status>
      <submissionId xsi:type="xsd:string">1164</submissionId>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>

```

IDAssignmentV3 Response – New ID Example

The sample below demonstrates the SOAP response to the above IDAssignmentV2 submission. The request did not include any data issues and there were no matches, so the response provided the new ID for assignment

```

<soapenv:Envelope
  xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"

```

```
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
            <assignIdReturn href="#id0"/>
        </ns1:assignIdResponse>
    </multiRef xmlns:ns2="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0"
        soapenc:root="0"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        xsi:type="ns2:IDAssignmentResultV3">
        <batchNumber xsi:type="xsd:string">266</batchNumber>
        <fieldsWithErrors xsi:nil="true" xsi:type="soapenc:Array"/>
        <potentialNearMatches xmlns:ns3="http://www.escholar.com"
            xsi:nil="true" xsi:type="ns3:NearMatchArray"/>
        <statePersonId xsi:type="xsd:string">5202763107</stateStudentId>
        <status xsi:type="xsd:string">05</status>
        <submissionId xsi:type="xsd:string">1164</submissionId>
    </multiRef>
</soapenv:Body>
</soapenv:Envelope
```

IDAssignmentV2 Request – Match List Found Example

The sample below demonstrates a SOAP request for a new ID assignment using the IDAssignmentV2 Web Service where matching records **were** found:

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:q0="http://com.escholar.ws" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <student xsi:type="q0:Student">
        <SSN xsi:type="xsd:string"/>
        <birthDate xsi:type="xsd:string">05/01/1988</birthDate>
        <districtCode xsi:type="xsd:string">123456</districtCode>
        <gender xsi:type="xsd:string">M</gender>
        <gradeLevel xsi:type="xsd:string">10</gradeLevel>
        <localStudentId xsi:type="xsd:string">3433322</localStudentId>
        <raceEthnicCode xsi:type="xsd:string">W</raceEthnicCode>
        <residentDistrictCode xsi:type="xsd:string">0009</residentDistrictCode>
        <schoolCode xsi:type="xsd:string">123456789</schoolCode>
        <schoolYear xsi:type="xsd:string">2007</schoolYear>
        <stateStudentId xsi:type="xsd:string"/>
        <studentFirstName xsi:type="xsd:string">Michael</studentFirstName>
        <studentLastName xsi:type="xsd:string">Jordin</studentLastName>
        <studentMiddleName xsi:type="xsd:string"/>
        <studentSuffix xsi:type="xsd:string"/>
      </student>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

IDAssignmentV3 Request – Match List Found Example

The sample below demonstrates a SOAP request for a new ID assignment using the IDAssignmentV3 Web Service where matching records **were** found:

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:q0="http://com.escholar.ws" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <student xsi:type="q0:Student">
        <SSN xsi:type="xsd:string"/>
        <birthDate xsi:type="xsd:string">05/01/1988</birthDate>
        <gender xsi:type="xsd:string">M</gender>
        <classification xsi:type="xsd:string">20</gradeLevel>
        <localPersonId xsi:type="xsd:string">1113322</localStudentId>
        <raceEthnicCode xsi:type="xsd:string">W</raceEthnicCode>
        <residentLocationCode xsi:type="xsd:string">0009</residentDistrictCode>
        <buildingCode xsi:type="xsd:string">123456789</schoolCode>
        <enrollmentYear xsi:type="xsd:string">2007</schoolYear>
        <statePersonId xsi:type="xsd:string"/>
        <firstName xsi:type="xsd:string">Mira</studentFirstName>
        <lastName xsi:type="xsd:string">Rauen</studentLastName>
        <middleName xsi:type="xsd:string"/>
        <nameSuffix xsi:type="xsd:string"/></student>
        <userId xsi:type="xsd:string">****</userId>
        <password xsi:type="xsd:string">****</password>
      </ns0:assignId>
    </soapenv:Body>
  </soapenv:Envelope>
```

IDAssignmentV2 Response – Match List Found Example

The sample below demonstrates the SOAP response to the above IDAssignmentV2 Match List Found sample. The request did not include any data issues and but did include matches. The near match list was returned, including a submission ID:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <multiRef xmlns:ns2="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0"
        soapenc:root="0"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        xsi:type="ns2:IDAssignmentResultV2">
        <batchNumber xsi:type="xsd:string">265</batchNumber>
        <fieldsWithErrors xsi:nil="true" xsi:type="soapenc:Array"/>
        <potentialNearMatches soapenc:arrayType="ns2:PotentialMatch[2]"
          xsi:type="soapenc:Array">
          <potentialNearMatches href="#id1"/>
          <potentialNearMatches href="#id2"/>
        </potentialNearMatches>
        <stateStudentId xsi:nil="true" xsi:type="xsd:string"/>
        <status xsi:type="xsd:string">06</status>
        <submissionId xsi:type="xsd:string">1163</submissionId>
      </multiRef>
      <multiRef xmlns:ns3="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id2"
        soapenc:root="0"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        xsi:type="ns3:PotentialMatch">
        <claimRequired xsi:type="xsd:boolean">>false</claimRequired>
        <comments xsi:type="xsd:string">null</comments>
        <creationDate xsi:type="xsd:dateTime">2007-11-
          15T13:21:19.000Z</creationDate>
        <districtCode xsi:type="xsd:string">123456</districtCode>
        <dob xsi:type="xsd:dateTime">1984-05-01T04:00:00.000Z</dob>
        <ethnicCode xsi:type="xsd:string">A</ethnicCode>
        <firstName xsi:type="xsd:string">MICHAEL</firstName>
        <gender xsi:type="xsd:string">M</gender>
        <gradeLevel xsi:type="xsd:string">03</gradeLevel>
        <lastName xsi:type="xsd:string">JORDIN</lastName>
        <matchProbability xsi:type="xsd:double">89.0</matchProbability>
        <middleName xsi:type="xsd:string">R</middleName>
        <relationType xsi:type="xsd:string">0</relationType>
        <schoolCode xsi:type="xsd:string">123456789</schoolCode>
        <schoolYear xsi:type="xsd:string">2006</schoolYear>
        <ssn xsi:type="xsd:string">863261269</ssn>
        <stateStudentID xsi:type="xsd:string">6039801123</stateStudentID>
        <suffixName xsi:type="xsd:string">JR</suffixName>
      </multiRef>
      <multiRef xmlns:ns4="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id1"
        soapenc:root="0"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
```

```

xsi:type="ns4:PotentialMatch">

  <claimRequired xsi:type="xsd:boolean">>false</claimRequired>
  <comments xsi:type="xsd:string">null</comments>
  <creationDate xsi:type="xsd:dateTime">2007-11-
    15T13:21:19.000Z</creationDate>
  <districtCode xsi:type="xsd:string">123456</districtCode>
  <dob xsi:type="xsd:dateTime">1999-05-01T04:00:00.000Z</dob>
  <ethnicCode xsi:type="xsd:string">A</ethnicCode>
  <firstName xsi:type="xsd:string">MICHAEL</firstName>
  <gender xsi:type="xsd:string">M</gender>
  <gradeLevel xsi:type="xsd:string">04</gradeLevel>
  <lastName xsi:type="xsd:string">JORDIN</lastName>
  <matchProbability xsi:type="xsd:double">89.0</matchProbability>
  <middleName xsi:type="xsd:string">R</middleName>
  <relationType xsi:type="xsd:string">0</relationType>
  <schoolCode xsi:type="xsd:string">123456789</schoolCode>
  <schoolYear xsi:type="xsd:string">2007</schoolYear>
  <ssn xsi:type="xsd:string">863261269</ssn>
  <stateStudentID xsi:type="xsd:string">2436954461</stateStudentID>
  <suffixName xsi:type="xsd:string">null</suffixName>
</multiRef>
</ns1:assignIdResponse>
</soapenv:Body>
</soapenv:Envelope>

```

IDAssignmentV3 Response – Match List Found Example

The sample below demonstrates the SOAP response to the above IDAssignmentV3 Match List Found sample. The request did not include any data issues and but did include matches. The near match list was returned, including a submission ID

```

<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <multiRef xmlns:ns2="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0"
        soapenc:root="0"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        xsi:type="ns2:IDAssignmentResultV3">
        <batchNumber xsi:type="xsd:string">265</batchNumber>
        <fieldsWithErrors xsi:nil="true" xsi:type="soapenc:Array"/>
        <potentialNearMatches soapenc:arrayType="ns2:PotentialMatch[2]"
          xsi:type="soapenc:Array">
          <potentialNearMatches href="#id1"/>
          <potentialNearMatches href="#id2"/>
        </potentialNearMatches>
        <stateStudentId xsi:nil="true" xsi:type="xsd:string"/>
        <status xsi:type="xsd:string">06</status>
        <submissionId xsi:type="xsd:string">1163</submissionId>
      </multiRef>
      <multiRef xmlns:ns3="http://com.escholar.ws"
        xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id2"
        soapenc:root="0"

```

```
soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
xsi:type="ns3:PotentialMatch">
  <claimRequired xsi:type="xsd:boolean">false</claimRequired>
  <comments xsi:type="xsd:string">null</comments>
  <creationDate xsi:type="xsd:dateTime">2007-11-
    15T13:21:19.000Z</creationDate>
  <locationCode xsi:type="xsd:string">123456</districtCode>
  <dob xsi:type="xsd:dateTime">1984-05-01T04:00:00.000Z</dob>
  <ethnicCode xsi:type="xsd:string">A</ethnicCode>
  <firstName xsi:type="xsd:string">MICHAEL</firstName>
  <gender xsi:type="xsd:string">M</gender>
  <classification xsi:type="xsd:string">03</gradeLevel>
  <lastName xsi:type="xsd:string">JORDIN</lastName>
  <matchProbability xsi:type="xsd:double">89.0</matchProbability>
  <relationType xsi:type="xsd:string">0</relationType>
  <buildingCode xsi:type="xsd:string">123456789</schoolCode>
  <enrollmentYear xsi:type="xsd:string">2006</schoolYear>
  <ssn xsi:type="xsd:string">863261269</ssn>
  <statePersonID xsi:type="xsd:string">6039801123</stateStudentID>
  <suffixName xsi:type="xsd:string">JR</suffixName>
</multiRef>
<multiRef xmlns:ns4="http://com.escholar.ws"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id1"
  soapenc:root="0"
  soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
  xsi:type="ns4:PotentialMatch">
  <claimRequired xsi:type="xsd:boolean">false</claimRequired>
  <comments xsi:type="xsd:string">null</comments>
  <creationDate xsi:type="xsd:dateTime">2007-11-
    15T13:21:19.000Z</creationDate>
  <locationCode xsi:type="xsd:string">123456</districtCode>
  <dob xsi:type="xsd:dateTime">1984-05-01T04:00:00.000Z</dob>
  <ethnicCode xsi:type="xsd:string">A</ethnicCode>
  <firstName xsi:type="xsd:string">MICHAEL</firstName>
  <gender xsi:type="xsd:string">M</gender>
  <classification xsi:type="xsd:string">03</gradeLevel>
  <lastName xsi:type="xsd:string">JORDIN</lastName>
  <matchProbability xsi:type="xsd:double">89.0</matchProbability>
  <relationType xsi:type="xsd:string">0</relationType>
  <buildingCode xsi:type="xsd:string">123456789</schoolCode>
  <enrollmentYear xsi:type="xsd:string">2006</schoolYear>
  <aliasId xsi:type="xsd:string">863261269</ssn>
  <statePersonID xsi:type="xsd:string">6039801123</stateStudentID>
  <suffixName xsi:type="xsd:string">JR</suffixName>
</multiRef>
</ns1:assignIdResponse>
</soapenv:Body>
</soapenv:Envelope>
```

NearMatchListV2 Request - Existing Near Match List

The sample below demonstrates a SOAP request for a Near Match List using the NearMatchListV2 Web Service. This example uses the submission information listed the “IDAssignmentV2 Response – Match List Found Example” above.

```
<?xml version="1.0" encoding="UTF-8"?>
  <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <soapenv:Body>
      <ns0:getNearMatches xmlns:ns0="http://ws.escholar.com"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
        <submissionId xsi:type="xsd:string">1163</submissionId>
        <userId xsi:type="xsd:string">****</userId>
        <password xsi:type="xsd:string">****</password>
      </ns0:getNearMatches>
    </soapenv:Body>
  </soapenv:Envelope>
```

NearMatchListV3 Request - Existing Near Match List

The sample below demonstrates a SOAP request for a Near Match List using the NearMatchListV2 Web Service. This example uses the submission information listed the “IDAssignmentV3 Response – Match List Found Example” above.

```
<?xml version="1.0" encoding="UTF-8"?>
  <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
    <soapenv:Body>
      <ns0:getNearMatches xmlns:ns0="http://ws.escholar.com"
        soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
        <submissionId xsi:type="xsd:string">1163</submissionId>
        <userId xsi:type="xsd:string">****</userId>
        <password xsi:type="xsd:string">****</password>
      </ns0:getNearMatches>
    </soapenv:Body>
  </soapenv:Envelope>
```

NearMatchListV2 Response – Existing Near Match List

This sample demonstrates the SOAP response for the above NearMatchListV2 request.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getNearMatchesResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <getNearMatchesReturn href="#id0"/>
    </ns1:getNearMatchesResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchListResult">
      <potentialNearMatches soapenc:arrayType="ns2:PotentialMatch[2]"
        xsi:type="soapenc:Array">
        <potentialNearMatches href="#id1"/>
        <potentialNearMatches href="#id2"/>
      </potentialNearMatches>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
    <multiRef xmlns:ns3="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id1" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns3:PotentialMatch">
      <claimRequired xsi:type="xsd:boolean">>false</claimRequired>
      <comments xsi:type="xsd:string">null</comments>
      <creationDate xsi:type="xsd:dateTime">2007-11-15T13:21:19.000Z</creationDate>
      <districtCode xsi:type="xsd:string">123456</districtCode>
      <dob xsi:type="xsd:dateTime">1999-05-01T04:00:00.000Z</dob>
      <ethnicCode xsi:type="xsd:string">A</ethnicCode>
      <firstName xsi:type="xsd:string">MICHAEL</firstName>
      <gender xsi:type="xsd:string">M</gender>
      <gradeLevel xsi:type="xsd:string">04</gradeLevel>
      <lastName xsi:type="xsd:string">JORDIN</lastName>
      <matchProbability xsi:type="xsd:double">89.0</matchProbability>
      <middleName xsi:type="xsd:string">R</middleName>
      <relationType xsi:type="xsd:string">0</relationType>
      <schoolCode xsi:type="xsd:string">123456789</schoolCode>
      <schoolYear xsi:type="xsd:string">2007</schoolYear>
      <ssn xsi:type="xsd:string">863261269</ssn>
      <stateStudentID xsi:type="xsd:string">2436954461</stateStudentID>
      <suffixName xsi:type="xsd:string">null</suffixName>
    </multiRef>
    <multiRef xmlns:ns4="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id2" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns4:PotentialMatch">
      <claimRequired xsi:type="xsd:boolean">>false</claimRequired>
      <comments xsi:type="xsd:string">null</comments>
      <creationDate xsi:type="xsd:dateTime">2007-11-
        15T13:21:19.000Z</creationDate>
      <districtCode xsi:type="xsd:string">123456</districtCode>
      <dob xsi:type="xsd:dateTime">1984-05-01T04:00:00.000Z</dob>
      <ethnicCode xsi:type="xsd:string">A</ethnicCode>
      <firstName xsi:type="xsd:string">MICHAEL</firstName>
    </multiRef>
  </Body>
</Envelope>
```

```

    <gender xsi:type="xsd:string">M</gender>
    <gradeLevel xsi:type="xsd:string">03</gradeLevel>
    <lastName xsi:type="xsd:string">JORDIN</lastName>
    <matchProbability xsi:type="xsd:double">89.0</matchProbability>
    <middleName xsi:type="xsd:string">R</middleName>
    <relationType xsi:type="xsd:string">0</relationType>
    <schoolCode xsi:type="xsd:string">123456789</schoolCode>
    <schoolYear xsi:type="xsd:string">2006</schoolYear>
    <ssn xsi:type="xsd:string">863261269</ssn>
    <stateStudentID xsi:type="xsd:string">6039801123</stateStudentID>
    <suffixName xsi:type="xsd:string">JR</suffixName>
  </multiRef>
</soapenv:Body>
</soapenv:Envelope>

```

NearMatchListV3 Response – Existing Near Match List

This sample demonstrates the SOAP response for the above NearMatchListV3 request.

```

<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <soapenv:Body>
    <ns1:getNearMatchesResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <getNearMatchesReturn href="#id0"/>
    </ns1:getNearMatchesResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchListResult">
      <potentialNearMatches soapenc:arrayType="ns2:PotentialMatch[2]"
        xsi:type="soapenc:Array">
        <potentialNearMatches href="#id1"/>
        <potentialNearMatches href="#id2"/>
      </potentialNearMatches>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
    <multiRef xmlns:ns3="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id1" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns3:PotentialMatch">
      <claimRequired xsi:type="xsd:boolean">>false</claimRequired>
      <comments xsi:type="xsd:string">null</comments>
      <creationDate xsi:type="xsd:dateTime">2007-11-15T13:21:19.000Z</creationDate>
      <locationCode xsi:type="xsd:string">123456</districtCode>
      <dob xsi:type="xsd:dateTime">1999-05-01T04:00:00.000Z</dob>
      <ethnicCode xsi:type="xsd:string">A</ethnicCode>
      <firstName xsi:type="xsd:string">MICHAEL</firstName>
      <gender xsi:type="xsd:string">M</gender>
      <lastName xsi:type="xsd:string">JORDIN</lastName>
      <matchProbability xsi:type="xsd:double">89.0</matchProbability>
      <relationType xsi:type="xsd:string">0</relationType>
      <buildingCode xsi:type="xsd:string">123456789</schoolCode>
      <enrollmentYear xsi:type="xsd:string">2007</schoolYear>
      <aliasId xsi:type="xsd:string">863261269</ssn>
      <statePersonID xsi:type="xsd:string">2436954461</stateStudentID>
      <suffixName xsi:type="xsd:string">null</suffixName>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>

```

```
</multiRef>
<multiRef xmlns:ns4="http://www.escholar.com"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id2" soapenc:root="0"
  soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
  xsi:type="ns4:PotentialMatch">
  <claimRequired xsi:type="xsd:boolean">false</claimRequired>
  <comments xsi:type="xsd:string">null</comments>
  <creationDate xsi:type="xsd:dateTime">2007-11-
    15T13:21:19.000Z</creationDate>
  <districtCode xsi:type="xsd:string">123456</districtCode>
  <dob xsi:type="xsd:dateTime">1984-05-01T04:00:00.000Z</dob>
  <ethnicCode xsi:type="xsd:string">A</ethnicCode>
  <firstName xsi:type="xsd:string">MICHAEL</firstName><gender
  xsi:type="xsd:string">M</gender>
  <gradeLevel xsi:type="xsd:string">03</gradeLevel>
  <lastName xsi:type="xsd:string">JORDIN</lastName>
  <matchProbability xsi:type="xsd:double">89.0</matchProbability>
  <middleName xsi:type="xsd:string">R</middleName>
  <relationType xsi:type="xsd:string">0</relationType>
  <schoolCode xsi:type="xsd:string">123456789</schoolCode>
  <schoolYear xsi:type="xsd:string">2006</schoolYear>
  <ssn xsi:type="xsd:string">863261269</ssn>
  <stateStudentID xsi:type="xsd:string">6039801123</stateStudentID>
  <suffixName xsi:type="xsd:string">JR</suffixName>
</multiRef>
</soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV2 Request – Create a New ID

This sample demonstrates a SOAP request to create a new ID from a near match list.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1184</tranSerialNumber>
      <stateStudentId xsi:type="xsd:string">6241478796</stateStudentId>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV3 Request – Create a New ID

This sample demonstrates a SOAP request to create a new ID from a near match list.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1184</tranSerialNumber>
```

```
<statePersonId xsi:type="xsd:string">6241478796</stateStudentId>
<userId xsi:type="xsd:string">****</userId>
<password xsi:type="xsd:string">****</password>
</ns0:assignId>
</soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV2 Response – Create a New ID

This sample demonstrates a SOAP response to create the new ID request above.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <assignIdReturn href="#id0"/>
    </ns1:assignIdResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchResolutionResult">
      <stateStudentId xsi:type="xsd:string">6241478796</stateStudentId>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV3 Response – Create a New ID

This sample demonstrates a SOAP response to create the new ID request above.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <assignIdReturn href="#id0"/>
    </ns1:assignIdResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchResolutionResult">
      <statePersonId xsi:type="xsd:string">6241478796</stateStudentId>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV2 Request – Assign ID

This sample demonstrates the SOAP request for the NearMatchResolutionV2 service for a submission ID that does not have pending near matches:

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1163</tranSerialNumber>
      <stateStudentId xsi:type="xsd:string"/>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV3 Request – Assign ID

This sample demonstrates the SOAP request for the NearMatchResolutionV3 service for a submission ID that does not have pending near matches:

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:assignId xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1163</tranSerialNumber>
      <statePersonId xsi:type="xsd:string"/>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:assignId>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV2 Response – Assign ID with Error

This sample demonstrates the SOAP response for the above no pending matches request.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <assignIdReturn href="#id0"/>
    </ns1:assignIdResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchResolutionResult">
      <stateStudentId xsi:nil="true" xsi:type="xsd:string"/>
      <status xsi:type="xsd:string">FAILED_STAGE_RECORD_NOT_PENDING_NEAR_MAT
      CH</status>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

```
</soapenv:Body>  
</soapenv:Envelope>
```

NearMatchResolutionV3 Response – Assign ID with Error

This sample demonstrates the SOAP response for the above no pending matches request.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"  
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-  
  instance">  
  <soapenv:Body>  
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"  
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">  
      <assignIdReturn href="#id0"/>  
    </ns1:assignIdResponse>  
    <multiRef xmlns:ns2="http://www.escholar.com"  
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"  
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"  
      xsi:type="ns2:NearMatchResolutionResult">  
      <statePersonId xsi:nil="true" xsi:type="xsd:string"/>  
      <status xsi:type="xsd:string">FAILED_STAGE_RECORD_NOT_PENDING_NEAR_MAT  
      CH</status>  
    </multiRef>  
  </soapenv:Body>  
</soapenv:Envelope>
```

NearMatchResolutionV2 Request – Cancel

This sample demonstrates a SOAP request to cancel a near match using the submission ID.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:cancel xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1163</tranSerialNumber>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:cancel>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV3 Request – Cancel

This sample demonstrates a SOAP request to cancel a near match using the submission ID.

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns0:cancel xmlns:ns0="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <tranSerialNumber xsi:type="xsd:string">1163</tranSerialNumber>
      <userId xsi:type="xsd:string">****</userId>
      <password xsi:type="xsd:string">****</password>
    </ns0:cancel>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV2 Response – Cancel

This sample demonstrates the SOAP response to a NearMatchResolutionV2 cancel request using the information from the "NearMatchResolutionV2 Request – Cancel" from above.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:cancelResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <cancelReturn href="#id0"/>
    </ns1:cancelResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchResolutionResult">
      <stateStudentId xsi:nil="true" xsi:type="xsd:string"/>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

NearMatchResolutionV3 Response – Cancel

This sample demonstrates the SOAP response to a NearMatchResolutionV2 cancel request using the information from the “NearMatchResolutionV2 Request – Cancel” from above.

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:cancelResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <cancelReturn href="#id0"/>
    </ns1:cancelResponse>
    <multiRef xmlns:ns2="http://www.escholar.com"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:NearMatchResolutionResult">
      <statePersonId xsi:nil="true" xsi:type="xsd:string"/>
      <status xsi:type="xsd:string">SUCCESS</status>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

Error Response Samples – Invalid Username/Password

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
  instance">
  <soapenv:Body>
    <ns1:assignIdResponse xmlns:ns1="http://ws.escholar.com"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
      <assignIdReturn href="#id0"/>
    </ns1:assignIdResponse>
    <multiRef xmlns:ns2="http://com.escholar.ws"
      xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" id="id0" soapenc:root="0"
      soapenv:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
      xsi:type="ns2:IDAssignmentResultV2">
      <batchNumber xsi:nil="true" xsi:type="xsd:string"/>
      <fieldsWithErrors xsi:nil="true" xsi:type="soapenc:Array"/>
      <potentialNearMatches xmlns:ns3="http://www.escholar.com" xsi:nil="true"
        xsi:type="ns3:NearMatchArray"/>
      <stateStudentId xsi:nil="true" xsi:type="xsd:string"/>
      <status xsi:type="xsd:string">FAILED_USER_NOT_FOUND_OR_INACTIVE</status>
      <submissionId xsi:nil="true" xsi:type="xsd:string"/>
    </multiRef>
  </soapenv:Body>
</soapenv:Envelope>
```

******NOTE: Username and password for above request statements not included for security purposes.**

Appendix B – WSDL for Web Services

BatchInfo WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<wSDL:definitions targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo"
xmlns:apachesoap="http://xml.apache.org/xml-soap"
xmlns:impl="https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo"
xmlns:intf="https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:tns1="http://www.escholar.com"
xmlns:wSDL="http://schemas.xmlsoap.org/wSDL/" xmlns:wSDLsoap="http://schemas.xmlsoap.org/wSDL/soap/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <!--
    WSDL created by Apache Axis version: 1.4
    Built on Apr 22, 2006 (06:55:48 PDT)
  -->
  <wSDL:types>
    <schema targetNamespace="http://www.escholar.com"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://schemas.xmlsoap.org/soap/encoding/" />
      <complexType name="BatchInfoResult">
        <sequence>
          <element name="batchNumber" type="xsd:long" />
          <element name="batchStatus" nillable="true" type="xsd:string" />
          <element name="nearMatchCount" type="xsd:long" />
          <element name="stateStudentId" nillable="true" type="xsd:string" />
          <element name="status" nillable="true" type="xsd:string" />
          <element name="totalNumberRecords" type="xsd:long" />
          <element name="transactionStatus" nillable="true" type="xsd:string" />
        </sequence>
      </complexType>
    </schema>
  </wSDL:types>
  <wSDL:message name="getBatchInformationResponse">
    <wSDL:part name="getBatchInformationReturn" type="tns1:BatchInfoResult" />
  </wSDL:message>
  <wSDL:message name="getBatchInformationRequest">
    <wSDL:part name="batchNumber" type="xsd:long" />
    <wSDL:part name="userId" type="xsd:string" />
    <wSDL:part name="password" type="xsd:string" />
  </wSDL:message>
  <wSDL:portType name="BatchInfo">
    <wSDL:operation name="getBatchInformation" parameterOrder="batchNumber userId password">
      <wSDL:input message="impl:getBatchInformationRequest"
name="getBatchInformationRequest" />
      <wSDL:output message="impl:getBatchInformationResponse"
name="getBatchInformationResponse" />
    </wSDL:operation>
  </wSDL:portType>
  <wSDL:binding name="BatchInfoSoapBinding" type="impl:BatchInfo">
    <wSDLsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http" />
    <wSDL:operation name="getBatchInformation">
      <wSDLsoap:operation soapAction="" />
      <wSDL:input name="getBatchInformationRequest">
        <wSDLsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://ws.escholar.com" use="encoded" />
      </wSDL:input>
    </wSDL:operation>
  </wSDL:binding>
</wSDL:definitions>
```

```
        <wsdl:output name="getBatchInformationResponse">
            <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo" use="encoded"/>
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="BatchInfoService">
    <wsdl:port binding="impl:BatchInfoSoapBinding" name="BatchInfo">
        <wsdlsoap:address
location="https://tea4avdplbprod.tea.state.tx.us/uid/services/BatchInfo"/>
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

IDAssignmentV2 WSDL, operation assigned

```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"
xmlns:apacheSOAP="http://xml.apache.org/xml-soap"
xmlns:impl="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"
xmlns:intf="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:tns1="http://www.escholar.com"
xmlns:tns2="http://util.java" xmlns:tns3="http://sql.java" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
xmlns:wSDLsoap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <!--
    WSDL created by Apache Axis version: 1.4
    Built on Apr 22, 2006 (06:55:48 PDT)
  -->
  <wsdl:types>
    <schema
targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import namespace="http://util.java"/>
      <import namespace="http://www.escholar.com"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="ArrayOf_xsd_string">
        <complexContent>
          <restriction base="soapenc:Array">
            <attribute ref="soapenc:arrayType"
wsdl:arrayType="xsd:string[]" />
          </restriction>
        </complexContent>
      </complexType>
    </schema>
    <schema targetNamespace="http://www.escholar.com"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import namespace="http://util.java"/>
      <import
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="StudentV2">
        <sequence>
          <element name="SSN" nillable="true" type="xsd:string"/>
          <element name="alternateId" nillable="true" type="xsd:string"/>
          <element name="alternateSource" nillable="true" type="xsd:string"/>
          <element name="birthDate" nillable="true" type="xsd:string"/>
          <element name="cdfNumbersArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
          <element name="cdfValuesArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
          <element name="districtCode" nillable="true" type="xsd:string"/>
          <element name="ethnicityIndicator" nillable="true" type="xsd:string"/>
          <element name="gender" nillable="true" type="xsd:string"/>
          <element name="gradeLevel" nillable="true" type="xsd:string"/>
          <element name="localStudentId" nillable="true" type="xsd:string"/>
          <element name="multiracialBinarySum" nillable="true"
type="xsd:double"/>
          <element name="previousLastName" nillable="true" type="xsd:string"/>
          <element name="race2Code" nillable="true" type="xsd:string"/>
        </sequence>
      </complexType>
    </schema>
  </wsdl:types>

```

```
<element name="race3Code" nillable="true" type="xsd:string"/>
<element name="race4Code" nillable="true" type="xsd:string"/>
<element name="race5Code" nillable="true" type="xsd:string"/>
<element name="raceEthnicCode" nillable="true" type="xsd:string"/>
<element name="recordUpdateDate" nillable="true" type="xsd:string"/>
<element name="recordUpdateDt" nillable="true" type="xsd:dateTime"/>
<element name="residentDistrictCode" nillable="true" type="xsd:string"/>
<element name="schoolCode" nillable="true" type="xsd:string"/>
<element name="schoolYear" nillable="true" type="xsd:string"/>
<element name="sourceSISCode" nillable="true" type="xsd:string"/>
<element name="stateStudentId" nillable="true" type="xsd:string"/>
<element name="studentFirstName" nillable="true" type="xsd:string"/>
<element name="studentLastName" nillable="true" type="xsd:string"/>
<element name="studentMiddleName" nillable="true" type="xsd:string"/>
<element name="studentSuffix" nillable="true" type="xsd:string"/>
</sequence>
</complexType>
<complexType name="PotentialMatchV2">
  <sequence>
    <element name="aliasId" nillable="true" type="xsd:string"/>
    <element name="alternateSource" nillable="true" type="xsd:string"/>
    <element name="cdfNumbersArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
    <element name="cdfRefNumber" nillable="true" type="xsd:decimal"/>
    <element name="cdfValuesArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
    <element name="claimRequired" type="xsd:boolean"/>
    <element name="comments" nillable="true" type="xsd:string"/>
    <element name="creationDate" nillable="true" type="xsd:anyType"/>
    <element name="districtCode" nillable="true" type="xsd:string"/>
    <element name="dob" nillable="true" type="xsd:dateTime"/>
    <element name="ethnicCode" nillable="true" type="xsd:string"/>
    <element name="ethnicCodeDesc" nillable="true" type="xsd:string"/>
    <element name="ethnicityIndicator" nillable="true" type="xsd:string"/>
    <element name="ethnicityIndicatorDesc" nillable="true"
type="xsd:string"/>
    <element name="firstName" nillable="true" type="xsd:string"/>
    <element name="gender" nillable="true" type="xsd:string"/>
    <element name="gradeLevel" nillable="true" type="xsd:string"/>
    <element name="lastName" nillable="true" type="xsd:string"/>
    <element name="matchProbability" type="xsd:double"/>
    <element name="middleName" nillable="true" type="xsd:string"/>
    <element name="multiracialBinarySum" nillable="true"
type="xsd:double"/>
    <element name="previousLastName" nillable="true" type="xsd:string"/>
    <element name="race2Code" nillable="true" type="xsd:string"/>
    <element name="race2CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race3Code" nillable="true" type="xsd:string"/>
    <element name="race3CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race4Code" nillable="true" type="xsd:string"/>
    <element name="race4CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race5Code" nillable="true" type="xsd:string"/>
    <element name="race5CodeDesc" nillable="true" type="xsd:string"/>
    <element name="relationType" nillable="true" type="xsd:string"/>
    <element name="schoolCode" nillable="true" type="xsd:string"/>
    <element name="schoolYear" nillable="true" type="xsd:string"/>
    <element name="sourceSISCode" nillable="true" type="xsd:string"/>
```

```

        <element name="ssn" nillable="true" type="xsd:string"/>
        <element name="stateStudentID" nillable="true" type="xsd:string"/>
        <element name="suffixName" nillable="true" type="xsd:string"/>
    </sequence>
</complexType>
<complexType name="NearMatchArray">
    <complexContent>
        <restriction base="soapenc:Array">
            <attribute ref="soapenc:arrayType"
wsdl:arrayType="tns1:PotentialMatchV2[]" />
        </restriction>
    </complexContent>
</complexType>
<complexType name="IDAssignmentResultV2">
    <sequence>
        <element name="aliasId" nillable="true" type="xsd:string"/>
        <element name="batchNumber" nillable="true" type="xsd:string"/>
        <element name="cdfMap" nillable="true" type="xsd:anyType"/>
        <element name="comments" nillable="true" type="xsd:string"/>
        <element name="fieldsWithErrors" nillable="true"
type="impl:ArrayOf_xsd_string"/>
        <element name="potentialNearMatches" nillable="true"
type="tns1:NearMatchArray"/>
        <element name="stateStudentId" nillable="true" type="xsd:string"/>
        <element name="status" nillable="true" type="xsd:string"/>
        <element name="submissionId" nillable="true" type="xsd:string"/>
    </sequence>
</complexType>
</schema>
</wsdl:types>
<wsdl:message name="assignIdRequest">
    <wsdl:part name="student" type="tns1:StudentV2"/>
    <wsdl:part name="userId" type="xsd:string"/>
    <wsdl:part name="password" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="assignIdResponse">
    <wsdl:part name="assignIdReturn" type="tns1:IDAssignmentResultV2"/>
</wsdl:message>
<wsdl:portType name="IDAssignmentV2">
    <wsdl:operation name="assignId" parameterOrder="student userId password">
        <wsdl:input message="impl:assignIdRequest" name="assignIdRequest"/>
        <wsdl:output message="impl:assignIdResponse" name="assignIdResponse"/>
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="IDAssignmentV2SoapBinding" type="impl:IDAssignmentV2">
    <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="assignId">
        <wsdlsoap:operation soapAction=""/>
        <wsdl:input name="assignIdRequest">
            <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
        </wsdl:input>
        <wsdl:output name="assignIdResponse">
            <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdp1bprod.tea.state.tx.us/uid/services/IDAssignmentV2" use="encoded"/>
        </wsdl:output>
    </wsdl:operation>

```

```
</wsdl:binding>  
<wsdl:service name="IDAssignmentV2Service">  
  <wsdl:port binding="impl:IDAssignmentV2SoapBinding" name="IDAssignmentV2">  
    <wsdlsoap:address  
location="https://tea4avdplbprod.tea.state.tx.us/uid/services/IDAssignmentV2"/>  
  </wsdl:port>  
</wsdl:service>  
</wsdl:definitions>
```

NearMatchListV2 WSDL, operation getNearMatches

```

<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"
xmlns:apachesoap="http://xml.apache.org/xml-soap"
xmlns:impl="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"
xmlns:intf="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:tns1="http://www.escholar.com"
xmlns:tns2="http://sql.java" xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/"
xmlns:wSDLsoap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <!--
    WSDL created by Apache Axis version: 1.4
    Built on Apr 22, 2006 (06:55:48 PDT)
  -->
  <wsdl:types>
    <schema
      targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"
      xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import namespace="http://www.escholar.com"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="ArrayOf_xsd_string">
        <complexContent>
          <restriction base="soapenc:Array">
            <attribute ref="soapenc:arrayType"
              wsdl:arrayType="xsd:string[]" />
          </restriction>
        </complexContent>
      </complexType>
    </schema>
    <schema targetNamespace="http://www.escholar.com"
      xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import
        namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="PotentialMatchV2">
        <sequence>
          <element name="aliasId" nillable="true" type="xsd:string"/>
          <element name="alternateSource" nillable="true" type="xsd:string"/>
          <element name="cdfNumbersArray" nillable="true"
            type="impl:ArrayOf_xsd_string"/>
          <element name="cdfRefNumber" nillable="true" type="xsd:decimal"/>
          <element name="cdfValuesArray" nillable="true"
            type="impl:ArrayOf_xsd_string"/>
          <element name="claimRequired" type="xsd:boolean"/>
          <element name="comments" nillable="true" type="xsd:string"/>
          <element name="creationDate" nillable="true" type="xsd:anyType"/>
          <element name="districtCode" nillable="true" type="xsd:string"/>
          <element name="dob" nillable="true" type="xsd:dateTime"/>
          <element name="ethnicCode" nillable="true" type="xsd:string"/>
          <element name="ethnicCodeDesc" nillable="true" type="xsd:string"/>
          <element name="ethnicityIndicator" nillable="true" type="xsd:string"/>
          <element name="ethnicityIndicatorDesc" nillable="true"
            type="xsd:string"/>
          <element name="firstName" nillable="true" type="xsd:string"/>
          <element name="gender" nillable="true" type="xsd:string"/>
        </sequence>
      </complexType>
    </schema>
  </wsdl:types>

```

```

    <element name="gradeLevel" nillable="true" type="xsd:string"/>
    <element name="lastName" nillable="true" type="xsd:string"/>
    <element name="matchProbability" type="xsd:double"/>
    <element name="middleName" nillable="true" type="xsd:string"/>
    <element name="multiracialBinarySum" nillable="true"
type="xsd:double"/>
    <element name="previousLastName" nillable="true" type="xsd:string"/>
    <element name="race2Code" nillable="true" type="xsd:string"/>
    <element name="race2CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race3Code" nillable="true" type="xsd:string"/>
    <element name="race3CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race4Code" nillable="true" type="xsd:string"/>
    <element name="race4CodeDesc" nillable="true" type="xsd:string"/>
    <element name="race5Code" nillable="true" type="xsd:string"/>
    <element name="race5CodeDesc" nillable="true" type="xsd:string"/>
    <element name="relationType" nillable="true" type="xsd:string"/>
    <element name="schoolCode" nillable="true" type="xsd:string"/>
    <element name="schoolYear" nillable="true" type="xsd:string"/>
    <element name="sourceSISCode" nillable="true" type="xsd:string"/>
    <element name="ssn" nillable="true" type="xsd:string"/>
    <element name="stateStudentID" nillable="true" type="xsd:string"/>
    <element name="suffixName" nillable="true" type="xsd:string"/>
  </sequence>
</complexType>
<complexType name="NearMatchArrayV2">
  <complexContent>
    <restriction base="soapenc:Array">
      <attribute ref="soapenc:arrayType"
wsdl:arrayType="tns1:PotentialMatchV2[]"/>
    </restriction>
  </complexContent>
</complexType>
<complexType name="NearMatchListResultV2">
  <sequence>
    <element name="potentialNearMatches" nillable="true"
type="tns1:NearMatchArrayV2"/>
    <element name="status" nillable="true" type="xsd:string"/>
  </sequence>
</complexType>
</schema>
</wsdl:types>
<wsdl:message name="getNearMatchesRequest">
  <wsdl:part name="submissionId" type="xsd:string"/>
  <wsdl:part name="userId" type="xsd:string"/>
  <wsdl:part name="password" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="getNearMatchesResponse">
  <wsdl:part name="getNearMatchesReturn" type="tns1:NearMatchListResultV2"/>
</wsdl:message>
<wsdl:portType name="NearMatchListV2">
  <wsdl:operation name="getNearMatches" parameterOrder="submissionId userId password">
    <wsdl:input message="impl:getNearMatchesRequest"
name="getNearMatchesRequest"/>
    <wsdl:output message="impl:getNearMatchesResponse"
name="getNearMatchesResponse"/>
  </wsdl:operation>
</wsdl:portType>

```

```
<wsdl:binding name="NearMatchListV2SoapBinding" type="impl:NearMatchListV2">
  <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
  <wsdl:operation name="getNearMatches">
    <wsdlsoap:operation soapAction=""/>
    <wsdl:input name="getNearMatchesRequest">
      <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
    </wsdl:input>
    <wsdl:output name="getNearMatchesResponse">
      <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2" use="encoded"/>
    </wsdl:output>
  </wsdl:operation>
</wsdl:binding>
<wsdl:service name="NearMatchListV2Service">
  <wsdl:port binding="impl:NearMatchListV2SoapBinding" name="NearMatchListV2">
    <wsdlsoap:address
location="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchListV2"/>
  </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

NearMatchResolutionV2 WSDL, operations: cancel, assignId, createNewId

```

<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2"
xmlns:apachesoap="http://xml.apache.org/xml-soap"
xmlns:impl="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2"
xmlns:intf="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:tns1="http://www.escholar.com"
xmlns:wSDL="http://schemas.xmlsoap.org/wsdl/" xmlns:wSDLsoap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <!--
    WSDL created by Apache Axis version: 1.4
    Built on Apr 22, 2006 (06:55:48 PDT)
  -->
  <wsdl:types>
    <schema targetNamespace="http://www.escholar.com"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://xml.apache.org/xml-soap"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="NearMatchResolutionResultV2">
        <sequence>
          <element name="aliasId" nillable="true" type="xsd:string"/>
          <element name="stateStudentId" nillable="true" type="xsd:string"/>
          <element name="status" nillable="true" type="xsd:string"/>
        </sequence>
      </complexType>
    </schema>
    <schema targetNamespace="http://xml.apache.org/xml-soap"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://www.escholar.com"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding"/>
      <complexType name="mapItem">
        <sequence>
          <element name="key" nillable="true" type="xsd:anyType"/>
          <element name="value" nillable="true" type="xsd:anyType"/>
        </sequence>
      </complexType>
      <complexType name="Map">
        <sequence>
          <element maxOccurs="unbounded" minOccurs="0" name="item"
type="apachesoap:mapItem"/>
        </sequence>
      </complexType>
    </schema>
  </wsdl:types>
  <wsdl:message name="assignIdResponse">
    <wsdl:part name="assignIdReturn" type="tns1:NearMatchResolutionResultV2"/>
  </wsdl:message>
  <wsdl:message name="cancelRequest">
    <wsdl:part name="tranSerialNumber" type="xsd:string"/>
    <wsdl:part name="stateStudentId" type="xsd:string"/>
    <wsdl:part name="userId" type="xsd:string"/>
    <wsdl:part name="password" type="xsd:string"/>
  </wsdl:message>
  <wsdl:message name="assignIdRequest">
    <wsdl:part name="tranSerialNumber" type="xsd:string"/>
    <wsdl:part name="stateStudentId" type="xsd:string"/>
  </wsdl:message>

```

```

        <wsdl:part name="userId" type="xsd:string"/>
        <wsdl:part name="password" type="xsd:string"/>
    </wsdl:message>
    <wsdl:message name="auditResolveNearMatchEntryRequest">
        <wsdl:part name="msg" type="xsd:string"/>
        <wsdl:part name="loginId" type="xsd:string"/>
        <wsdl:part name="p" type="apachesoap:Map"/>
    </wsdl:message>
    <wsdl:message name="cancelResponse">
        <wsdl:part name="cancelReturn" type="tns1:NearMatchResolutionResultV2"/>
    </wsdl:message>
    <wsdl:message name="createNewIdResponse">
        <wsdl:part name="createNewIdReturn" type="tns1:NearMatchResolutionResultV2"/>
    </wsdl:message>
    <wsdl:message name="createNewIdRequest">
        <wsdl:part name="tranSerialNumber" type="xsd:string"/>
        <wsdl:part name="stateStudentId" type="xsd:string"/>
        <wsdl:part name="userId" type="xsd:string"/>
        <wsdl:part name="password" type="xsd:string"/>
    </wsdl:message>
    <wsdl:message name="auditResolveNearMatchEntryResponse"></wsdl:message>
    <wsdl:portType name="NearMatchResolutionV2">
        <wsdl:operation name="cancel" parameterOrder="tranSerialNumber stateStudentId userId
password">
            <wsdl:input message="impl:cancelRequest" name="cancelRequest"/>
            <wsdl:output message="impl:cancelResponse" name="cancelResponse"/>
        </wsdl:operation>
        <wsdl:operation name="assignId" parameterOrder="tranSerialNumber stateStudentId userId
password">
            <wsdl:input message="impl:assignIdRequest" name="assignIdRequest"/>
            <wsdl:output message="impl:assignIdResponse" name="assignIdResponse"/>
        </wsdl:operation>
        <wsdl:operation name="createNewId" parameterOrder="tranSerialNumber stateStudentId userId
password">
            <wsdl:input message="impl:createNewIdRequest" name="createNewIdRequest"/>
            <wsdl:output message="impl:createNewIdResponse" name="createNewIdResponse"/>
        </wsdl:operation>
        <wsdl:operation name="auditResolveNearMatchEntry" parameterOrder="msg loginId p">
            <wsdl:input message="impl:auditResolveNearMatchEntryRequest"
name="auditResolveNearMatchEntryRequest"/>
            <wsdl:output message="impl:auditResolveNearMatchEntryResponse"
name="auditResolveNearMatchEntryResponse"/>
        </wsdl:operation>
    </wsdl:portType>
    <wsdl:binding name="NearMatchResolutionV2SoapBinding" type="impl:NearMatchResolutionV2">
        <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
        <wsdl:operation name="cancel">
            <wsdlsoap:operation soapAction=""/>
            <wsdl:input name="cancelRequest">
                <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
            </wsdl:input>
            <wsdl:output name="cancelResponse">
                <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2" use="encoded"/>
            </wsdl:output>
        </wsdl:operation>

```

```
<wsdl:operation name="assignId">
  <wsdlsoap:operation soapAction=""/>
  <wsdl:input name="assignIdRequest">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
  </wsdl:input>
  <wsdl:output name="assignIdResponse">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2" use="encoded"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="createNewId">
  <wsdlsoap:operation soapAction=""/>
  <wsdl:input name="createNewIdRequest">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
  </wsdl:input>
  <wsdl:output name="createNewIdResponse">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2" use="encoded"/>
  </wsdl:output>
</wsdl:operation>
<wsdl:operation name="auditResolveNearMatchEntry">
  <wsdlsoap:operation soapAction=""/>
  <wsdl:input name="auditResolveNearMatchEntryRequest">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
  </wsdl:input>
  <wsdl:output name="auditResolveNearMatchEntryResponse">
    <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2" use="encoded"/>
  </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="NearMatchResolutionV2Service">
  <wsdl:port binding="impl:NearMatchResolutionV2SoapBinding"
name="NearMatchResolutionV2">
    <wsdlsoap:address
location="https://tea4avdplbprod.tea.state.tx.us/uid/services/NearMatchResolutionV2"/>
  </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

StudentSearch WSDL, operations: searchStudent and searchWithIDExactMatch

```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="http://localhost:8080/uid/services/StudentSearch"
xmlns:apacheSOAP="http://xml.apache.org/xml-soap" xmlns:impl="http://localhost:8080/uid/services/StudentSearch"
xmlns:intf="http://localhost:8080/uid/services/StudentSearch"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:tns1="http://www.escholar.com"
xmlns:tns2="http://util.java" xmlns:tns3="http://sql.java" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
xmlns:wSDLsoap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <wsdl:types>
    <schema targetNamespace="http://localhost:8080/uid/services/StudentSearch"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import namespace="http://util.java"/>
      <import namespace="http://www.escholar.com"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding/" />
      <complexType name="ArrayOf_xsd_string">
        <complexContent>
          <restriction base="soapenc:Array">
            <attribute ref="soapenc:arrayType" wsdl:arrayType="xsd:string[]" />
          </restriction>
        </complexContent>
      </complexType>
    </schema>
    <schema targetNamespace="http://www.escholar.com"
xmlns="http://www.w3.org/2001/XMLSchema">
      <import namespace="http://sql.java"/>
      <import namespace="http://util.java"/>
      <import namespace="http://localhost:8080/uid/services/StudentSearch"/>
      <import namespace="http://schemas.xmlsoap.org/soap/encoding/" />
      <complexType name="StudentV2">
        <sequence>
          <element name="SSN" nillable="true" type="xsd:string"/>
          <element name="alternateId" nillable="true" type="xsd:string"/>
          <element name="alternateSource" nillable="true" type="xsd:string"/>
          <element name="birthDate" nillable="true" type="xsd:string"/>
          <element name="cdfNumbersArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
          <element name="cdfValuesArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
          <element name="districtCode" nillable="true" type="xsd:string"/>
          <element name="ethnicityIndicator" nillable="true" type="xsd:string"/>
          <element name="gender" nillable="true" type="xsd:string"/>
          <element name="gradeLevel" nillable="true" type="xsd:string"/>
          <element name="localStudentId" nillable="true" type="xsd:string"/>
          <element name="multiracialBinarySum" nillable="true" type="xsd:double"/>
          <element name="previousLastName" nillable="true" type="xsd:string"/>
          <element name="race2Code" nillable="true" type="xsd:string"/>
          <element name="race3Code" nillable="true" type="xsd:string"/>
          <element name="race4Code" nillable="true" type="xsd:string"/>
          <element name="race5Code" nillable="true" type="xsd:string"/>
          <element name="raceEthnicCode" nillable="true" type="xsd:string"/>
          <element name="recordUpdateDate" nillable="true" type="xsd:string"/>
          <element name="recordUpdateDt" nillable="true" type="xsd:dateTime"/>
          <element name="residentDistrictCode" nillable="true" type="xsd:string"/>
          <element name="schoolCode" nillable="true" type="xsd:string"/>
          <element name="schoolYear" nillable="true" type="xsd:string"/>
          <element name="sourceSISCode" nillable="true" type="xsd:string"/>
          <element name="stateStudentId" nillable="true" type="xsd:string"/>
        </sequence>
      </complexType>
    </schema>
  </wsdl:types>

```

```

<element name="studentFirstName" nillable="true" type="xsd:string"/>
<element name="studentLastName" nillable="true" type="xsd:string"/>
<element name="studentMiddleName" nillable="true" type="xsd:string"/>
<element name="studentSuffix" nillable="true" type="xsd:string"/>
</sequence>
</complexType>
<complexType name="PotentialMatchV2">
<sequence>
<element name="aliasId" nillable="true" type="xsd:string"/>
<element name="alternateSource" nillable="true" type="xsd:string"/>
<element name="cdfNumbersArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
<element name="cdfRefNumber" nillable="true" type="xsd:decimal"/>
<element name="cdfValuesArray" nillable="true"
type="impl:ArrayOf_xsd_string"/>
<element name="claimRequired" type="xsd:boolean"/>
<element name="comments" nillable="true" type="xsd:string"/>
<element name="creationDate" nillable="true" type="xsd:anyType"/>
<element name="districtCode" nillable="true" type="xsd:string"/>
<element name="dob" nillable="true" type="xsd:dateTime"/>
<element name="ethnicCode" nillable="true" type="xsd:string"/>
<element name="ethnicCodeDesc" nillable="true" type="xsd:string"/>
<element name="ethnicityIndicator" nillable="true" type="xsd:string"/>
<element name="ethnicityIndicatorDesc" nillable="true" type="xsd:string"/>
<element name="firstName" nillable="true" type="xsd:string"/>
<element name="gender" nillable="true" type="xsd:string"/>
<element name="gradeLevel" nillable="true" type="xsd:string"/>
<element name="lastName" nillable="true" type="xsd:string"/>
<element name="matchProbability" type="xsd:double"/>
<element name="middleName" nillable="true" type="xsd:string"/>
<element name="multiracialBinarySum" nillable="true" type="xsd:double"/>
<element name="previousLastName" nillable="true" type="xsd:string"/>
<element name="race2Code" nillable="true" type="xsd:string"/>
<element name="race2CodeDesc" nillable="true" type="xsd:string"/>
<element name="race3Code" nillable="true" type="xsd:string"/>
<element name="race3CodeDesc" nillable="true" type="xsd:string"/>
<element name="race4Code" nillable="true" type="xsd:string"/>
<element name="race4CodeDesc" nillable="true" type="xsd:string"/>
<element name="race5Code" nillable="true" type="xsd:string"/>
<element name="race5CodeDesc" nillable="true" type="xsd:string"/>
<element name="relationType" nillable="true" type="xsd:string"/>
<element name="schoolCode" nillable="true" type="xsd:string"/>
<element name="schoolYear" nillable="true" type="xsd:string"/>
<element name="sourceSISCode" nillable="true" type="xsd:string"/>
<element name="ssn" nillable="true" type="xsd:string"/>
<element name="stateStudentID" nillable="true" type="xsd:string"/>
<element name="suffixName" nillable="true" type="xsd:string"/>
</sequence>
</complexType>
<complexType name="NearMatchArray">
<complexContent>
<restriction base="soapenc:Array">
<attribute ref="soapenc:arrayType"
wsdl:arrayType="tns1:PotentialMatchV2[]"/>
</restriction>
</complexContent>
</complexType>
</complexType name="StudentSearchResult">

```

```

        <sequence>
            <element name="aliasId" nillable="true" type="xsd:string"/>
            <element name="batchNumber" nillable="true" type="xsd:string"/>
            <element name="cdfMap" nillable="true" type="xsd:anyType"/>
            <element name="fieldsWithErrors" nillable="true"
type="impl:ArrayOf_xsd_string"/>
            <element name="potentialNearMatches" nillable="true"
type="tns1:NearMatchArray"/>
            <element name="stateStudentId" nillable="true" type="xsd:string"/>
            <element name="status" nillable="true" type="xsd:string"/>
            <element name="submissionId" nillable="true" type="xsd:string"/>
        </sequence>
    </complexType>
</schema>
</wsdl:types>
<wsdl:message name="searchStudentResponse">
    <wsdl:part name="searchStudentReturn" type="tns1:StudentSearchResult"/>
</wsdl:message>
<wsdl:message name="searchWithIDExactMatchRequest">
    <wsdl:part name="student" type="tns1:StudentV2"/>
    <wsdl:part name="userId" type="xsd:string"/>
    <wsdl:part name="password" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="searchStudentRequest">
    <wsdl:part name="student" type="tns1:StudentV2"/>
    <wsdl:part name="userId" type="xsd:string"/>
    <wsdl:part name="password" type="xsd:string"/>
</wsdl:message>
<wsdl:message name="searchWithIDExactMatchResponse">
    <wsdl:part name="searchWithIDExactMatchReturn" type="tns1:StudentSearchResult"/>
</wsdl:message>
<wsdl:portType name="StudentSearch">
    <wsdl:operation name="searchWithIDExactMatch" parameterOrder="student userId password">
        <wsdl:input message="impl:searchWithIDExactMatchRequest"
name="searchWithIDExactMatchRequest"/>
        <wsdl:output message="impl:searchWithIDExactMatchResponse"
name="searchWithIDExactMatchResponse"/>
    </wsdl:operation>
    <wsdl:operation name="searchStudent" parameterOrder="student userId password">
        <wsdl:input message="impl:searchStudentRequest" name="searchStudentRequest"/>
        <wsdl:output message="impl:searchStudentResponse" name="searchStudentResponse"/>
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="StudentSearchSoapBinding" type="impl:StudentSearch">
    <wsdlsoap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="searchWithIDExactMatch">
        <wsdlsoap:operation soapAction=""/>
        <wsdl:input name="searchWithIDExactMatchRequest">
            <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
        </wsdl:input>
        <wsdl:output name="searchWithIDExactMatchResponse">
            <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://localhost:8080/uid/services/StudentSearch" use="encoded"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="searchStudent">
        <wsdlsoap:operation soapAction=""/>
    </wsdl:operation>

```

```
<wsdl:input name="searchStudentRequest">
  <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://wsv2.escholar.com" use="encoded"/>
</wsdl:input>
<wsdl:output name="searchStudentResponse">
  <wsdlsoap:body encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
namespace="http://localhost:8080/uid/services/StudentSearch" use="encoded"/>
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="StudentSearchService">
  <wsdl:port binding="impl:StudentSearchSoapBinding" name="StudentSearch">
    <wsdlsoap:address location="http://localhost:8080/uid/services/StudentSearch"/>
  </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```

Appendix C – WADL for RESTful Web Services

```
<application xmlns="http://wadl.dev.java.net/2009/02">
<doc xmlns:jersey="http://jersey.java.net/" jersey:generatedBy="Jersey: 1.12 02/15/2012 05:30
PM"/>
<grammars>
<include href="xsd0.xsd">
<doc title="Generated" xml:lang="en"/>
</include>
</grammars>
<resources base="http://localhost:9090/uid/rest/">
<resource path="NearMatchListV2R">
<resource path="getNearMatches">
<method id="getNearMatches" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="submissionId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wadl.dev.java.net/2009/02" xmlns=""
element="NearMatchListResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="NearMatchListV3">
<resource path="getNearMatches">
<method id="getNearMatches" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="submissionId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wadl.dev.java.net/2009/02" xmlns=""
element="NearMatchListResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="BatchInfoV2R">
<resource path="getBatchInformation">
<method id="getBatchInformation" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="batchNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
```

```
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="BatchInfoResult" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="NearMatchResolutionV2R">
<resource path="cancel">
<method id="cancel" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="stateStudentId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
<resource path="assignId">
<method id="assignId" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="stateStudentId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
<resource path="createNewId">
<method id="createNewId" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="stateStudentId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
```

```
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="StudentSearchV2R">
<resource path="searchWithIDExactMatch">
<method id="searchWithIDExactMatch" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="StudentV2R" mediaType="application/xml"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="StudentSearchResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
<resource path="searchStudent">
<method id="searchStudent" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="StudentV2R" mediaType="application/xml"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="StudentSearchResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="NearMatchResolutionV3">
<resource path="cancel">
<method id="cancel" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="statePersonId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
```

```
<resource path="assignId">
<method id="assignId" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="statePersonId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
<resource path="createNewId">
<method id="createNewId" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="tranSerialNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="statePersonId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="NearMatchResolutionResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="PersonSearchV3">
<resource path="searchWithIDExactMatch">
<method id="searchWithIDExactMatch" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="PersonV3" mediaType="application/xml"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="PersonSearchResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
<resource path="searchPerson">
<method id="searchPerson" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="PersonV3" mediaType="application/xml"/>
```

```
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="PersonSearchResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="IDAssignmentV2R">
<resource path="assignId">
<method id="assignIdV2R" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="StudentV2R" mediaType="application/xml"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="IDAssignmentResultV2R" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="BatchInfoV3">
<resource path="getBatchInformation">
<method id="getBatchInformation" name="GET">
<request>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="batchNumber" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="userId" style="query"
type="xs:string"/>
<param xmlns:xs="http://www.w3.org/2001/XMLSchema" name="password" style="query"
type="xs:string"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="BatchInfoResult" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
<resource path="IDAssignmentV3">
<resource path="assignId">
<method id="assignId" name="POST">
<request>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="PersonV3" mediaType="application/xml"/>
</request>
<response>
<ns2:representation xmlns:ns2="http://wabl.dev.java.net/2009/02" xmlns=""
element="IDAssignmentResultV3" mediaType="application/xml"/>
</response>
</method>
</resource>
</resource>
</resources>
```

</application>

Appendix D – IDAssignmentV2 Code Basic Example (VB)

The code below is a basic example of the IDAssignmentV2 Web Service in Visual Basic.

```
Public Sub Button1_Click(ByVal sender As System.Object, ByVal e As
System.EventArgs) Handles Button1.Click
    'create new IDAssignmentV2 web service
    Dim Service As DEMO.IDAssignmentService = New
DEMO.IDAssignmentService()
    'create new object for input and new result object
    Dim student As DEMO.Student = New DEMO.Student
    Dim StudentInformation As DEMO.IDAssignmentResultV2

    'set the student object from field values
    student.birthDate = DOB.Text
    student.studentFirstName = FirstName.Text
    student.studentLastName = LastName.Text
    student.gradeLevel = GradeLevel.Text
    student.districtCode = DistrictCode.Text
    student.raceEthnicCode = EthnicCode.Text
    student.schoolYear = SchoolYear.Text
    student.residentDistrictCode = ResidentDistrict.Text
    student.schoolCode = SchoolCode.Text
    student.gender = Gender.Text
    student.localStudentId = Localid.Text
    student.studentMiddleName = MiddleName.Text
    student.stateStudentId = StateID.Text

    'call the WS using the super user account username and password
    StudentInformation = Service.assignId(student, "abcd", "abcd")

    'write out details
    Response.Write("Batch Num:" & StudentInformation.batchNumber)
    Response.Write("<BR>")
    Response.Write(StudentInformation.status)
    Response.Write("<BR>Submission ID: ")
    Response.Write(StudentInformation.submissionId)
    Response.Write("<BR>State ID: ")
    Response.Write(StudentInformation.stateStudentId)
    Response.Write("<BR>")

    'write out all of the potential matches if they exists
    If Not (StudentInformation.potentialNearMatches()) Is Nothing Then
        Dim x As Long
        For x = LBound(StudentInformation.potentialNearMatches()) To
            UBound(StudentInformation.potentialNearMatches())
            Response.Write("Claims: ")
            Response.Write(StudentInformation.potentialNearMatches(x).claimRequired())
            Response.Write("<BR>Comments: ")
            Response.Write(StudentInformation.potentialNearMatches(x).comments())
            Response.Write("<BR>Create Date: ")
            Response.Write(StudentInformation.potentialNearMatches(x).creationDate)
            Response.Write("<BR>District Code: ")
            Response.Write(StudentInformation.potentialNearMatches(x).districtCode())
            Response.Write("<BR>Date of Birth: ")
            Response.Write(StudentInformation.potentialNearMatches(x).dob())
            Response.Write("<BR>Ethnic Code: ")
            Response.Write(StudentInformation.potentialNearMatches(x).ethnicCode())
            Response.Write("<BR>First Name: ")
            Response.Write(StudentInformation.potentialNearMatches(x).firstName())
            Response.Write("<BR>Gender: ")
        Next
    End If
End Sub
```

```
        Response.Write(StudentInformation.potentialNearMatches(x).gender())
        Response.Write("<BR>Grade Level: ")
    End If

    Response.Write(StudentInformation.potentialNearMatches(x).gradeLevel())
    Response.Write("<BR>Last Name: ")
    Response.Write(StudentInformation.potentialNearMatches(x).lastName())
    Response.Write("<BR>Match Probability: ")
    Response.Write(StudentInformation.potentialNearMatches(x).matchProbability())
    Response.Write("<BR>Middle Name: ")
    Response.Write(StudentInformation.potentialNearMatches(x).middleName())
    Response.Write("<BR>School Code: ")
    Response.Write(StudentInformation.potentialNearMatches(x).schoolCode())
    Response.Write("<BR>School Year: ")
    Response.Write(StudentInformation.potentialNearMatches(x).schoolYear())
    Response.Write("<BR>SSN: ")
    Response.Write(StudentInformation.potentialNearMatches(x).ssn())
    Response.Write("<BR>State Student ID: ")
    Response.Write(StudentInformation.potentialNearMatches(x).stateStudentID())
    Response.Write("<BR>Suffix: ")
    Response.Write(StudentInformation.potentialNearMatches(x).suffixName()) Next

    'write out individual fields with errors if validation
    error exists If Not (StudentInformation.fieldsWithErrors())
    Is Nothing Then
        Response.Write("Error(s):
        <BR> ") Dim i As Long

    End If End Sub

'write out all of the fields
For i = LBound(StudentInformation.fieldsWithErrors()) To
    UBound(StudentInformation.fieldsWithErrors())
    Response.Write(StudentInformation.fieldsWithErrors(i)) Response.Write("<BR>")
Next
```